

LOCATION MAP

MAINE TURNPIKE AUTHORITY

 $\frac{\mathcal{A} \mathcal{M} \mathcal{M} \mathcal{A}}{\mathcal{A}} = \frac{\partial 7}{\partial 2} \frac{18}{18}$ $\frac{\mathcal{A}}{\mathcal{A}} = \frac{\partial 7}{\partial 2} \frac{18}{18}$ $\frac{\mathcal{A}}{\mathcal{A}} = \frac{1}{2} \frac{18}{18}$ $\frac{1}{2} \frac{18}{18}$ $\frac{1}{2} \frac{18}{18}$

MAINE

TURNPIKE

THE GOLD STAR

MEMORIAL HIGHWAY

DANIEL E. WATHEN, CHAIR

ROBERT D. STONE, VICE CHAIR

MICHAEL J. CIANCHETTE, MEMBER

JOHN E. DORITY, MEMBER

ANN R. ROBINSON, MEMBER

THOMAS J. ZUKE, MEMBER

KAREN S. DOYLE, MEMBER EX-OFFICIO

S. PETER MILLS, EXECUTIVE DIRECTOR

CONTRACT 2018.18

MILE 25.5 SB AND NB

PPROVED:

INDEX OF SHEETS

DESCRIPTION TITLE SHEET ESTIMATED QUANTITIES GENERAL NOTES SURVEY CONTROL PLAN SITE TYPICAL SECTIONS MISCELLANEOUS DETAILS MAINTENANCE OF TRAFFIC SIGN SUMMARY FINAL SITE PLANS PROFILES. GRADING AND DRAINAGE PLANS

LIMIT OF DISTURBANCE PLAN

STRUCTURAL PLANS

CANOPY PLAN AND ELEVATION CONCRETE SLAB AND ISLANDS AT GASOLINE DISPENSERS CONCRETE ISLAND 2 CANOPY COLUMN AND BUMPER DETAILS CONCRETE SLAB AND ISLANDS AT DIESEL DISPENSERS SOUTHBOUND CONCRETE SLABS AT STORAGE TANKS NORTHBOUND CONCRETE SLAB AT STORAGE TANK SLAB DETAILS REINFORCING SCHEDULE

FUEL SYSTEM PLANS

SOUTHBOUND TEMPORARY GAS/DIESEL PIPING PLAN EXISTING GAS/DIESEL DEMOLITION PLAN PROPOSED GAS/DIESEL PIPING

NORTHBOUND TEMPORARY GAS/DIESEL PIPING PLAN EXISTING GAS/DIESEL DEMOLITION PLAN PROPOSED GAS/DIESEL PIPING

FUEL TANK DETAILS

2018.18 CONTRACT





une C. Lovelles

6/28/18

ITEM NO.	ITEMDESCRIPTION	UNIT	NB PLAZA	SB PLAZA	TOTAL QUANTITY	ITEM
202.15	Remove Existing Manhole or Catch Basin	EA	0	1	- I	615.07
202.17	Removing Existing Structural Concrete	LS	0.5	0.5	1	618.13
202.202	Removing Pavement Surface	SY	810	480	1,250	619.12
203.20	Common Excavation	CY	2780	2010	4,790	619.12
203.2312	Health and Safety Plan	LS	0.5	0.5	1	622.10
203.2333	Disposal/Treatment of Special Excavation	TON	3000	3000	6,000	626.13
203.2334	Disposal/Treatment of Contaminated Groundwater	LS	0,5	0.5	1	626.22
206.061	Structrural Earth Excavation - Drainage Minor Structures Below Grade	CY	25	25	50	626.32
304.10	Aggregate Subbase Course - Gravel	CY	2500	1950	4,450	626.36
304.14	Aggregate Base Course - Type A	CY	1145	840	1,985	627.18
403.207	Hot Mix Asphalt, 19.0 mm Nominal Maximum Size	Ton	1100	820	1,920	627.73
403.208	Hot Mix Asphalt, 12.5 mm Nominal Maximum Size	Ton	700	500	1,200	627.73
	Hot Mix Asphalt, 12.5 mm Nominal Maximum Size (sidewalks, drives, islands &	1.1.1				627.74
403.2084	incidentals)	Ton	27	30	57	629.05
403.213	Hot Mix Asphalt, 12.5 mm Nominal Maximum Size (Base and Intermediate Base course)	Ton	700	480	1,180	631.12 631.17
409.15	Bituminous Tack Coat, Applied	Gal	660	480	1,140	631.22
419.30	Sawing Bituminous Pavement	LF	1,500	860	2,360	631.36
502.701	Concrete Gas Island and Slab	CY	110	110	220	634.20
502.702	Concrete Diesel Island and Slab	CY	80	80	160	634.22
502.703	Concrete Gas Tank Slab	CY		45	45	634.23
502.704	Concrete Diesel Tank Slab	CY		18	18	639.19
502.705	Concrete Fuel Tank Slab	CY	60		60	639.19
503.14	Epoxy-Coated Reinforcing Steel, Fabricated and Delivered	LB	21,000	21,000	42,000	645.10
503.15	Epoxy-Coated Reinforcing Steel, Placing	LB	21,000	21,000	42,000	652.31
524.30	Temporary Structural Support	EA	2	2	4	652.33
526.306	Temporary Concrete Barrier, Type I - Supplied by Authority (950 LF)	LS	0.5	0.5	1	652.34
527.34	Work Zone Crash Cushion - TL-2	EA	2	2	4	652.35
603.155	12 Inch Reinforced Concrete Pipe - Class III	LF	270	200	470	652.36
603.165	15 inch Reinforced Concrete Pipe - Class III	LF	130	260	390	652.38
604.071	Catch Basin Type A1	EA	2	3	5	652.41
604.09	Catch Basin Type B1	EA	0	1	1	655.10
604.15	Manhole	EA	0	1	1	655.11
604.18	Adjusting Manhole or Catch Basin To Grade	EA	2	3	5	656.50
604.182	Cleaning Existing Catch Basin and Manhole	EA	1	0	1	656.63
604.246	Catch Basin Type F5	EA	2	0	2	659.10
604.30	Oil-water Separator System	EA	1	1	2	800.01
606.356	Underdrain Delineator Post	EA	1	0	1	800.02
607.18	6 Foot Chain Link Safety Fence	LF	200	200	400	800.03
608.08	Reinforced Concrete Sidewalk	SY	0	9	9	800.04
609.11	Vertical Curb Type 1	LF	180	350	530	800.05
609.12	Vertical Curb Type 1 - Circular	LF	17	26	43	800.06
609.234	Terminal Curb Type 1 - 4 Foot	EA	2	0	.2	800.07
609.38	Reset Curb Type 1	LF	690	450	1,140	800.08
610.08	Plain Riprap	CY	3	0	3	800.20
613.319	Erosion Control Blanket	SY	12	0	12	800.21

ITEM NO.	ITEM DESCRIPTION	UNIT	NB PLAZA	SB PLAZA	TOTAL QUANTITY
615.07	Loam	CY	170	70	240
518.13	Seeding Method Number 1	Unit	14	6	20
519.1201	Mulch - Plan Quantity	Unit	14	6	20
519.1202	Temporary Mulch	LS	0.5	0.5	1
522.10	Transplanting Shrub	EA	0	4	4
526.13	18" x 12" x 18" Quazite Junction Box	EA	- 4	2	6
526.22	Non-metallic Conduit	LF	540	410	950
526.32	24 inch Diameter Foundation	EA	2	1	3
526.36	Remove or Modify Concrete Foundation	EA	2	1	3
527.18	12 inch Solid White Pavement Marking Line	LF	0	16	16
527.731	Temporary 6 Inch Black Pavement Marking Tape	LF	810	1250	2,060
527.733	4" White or Yellow Painted Pavement Marking Line	LF	250	250	500
527.744	6" White or Yellow Painted Pavement Marking Line	LF	250	250	500
529.05	Hand Labor, Straight Time	MH	20	20	40
531.12	All Purpose Excavator (including operator)	HR	20	20	40
531.172	Truck Large (including operator)	HR	40	40	80
531.221	Small Front End Loader (Including Operator)	HR	20	20	40
531.36	Foreman	HR	20	20	40
534.208	Remove and Reset Light Standards	EA	2	1	3
534.22	Temporary Lighting (SB Plaza)	LS		1	1
534.23	Temporary Lighting (NB Plaza)	LS	1	1 m m	1
539.19	Field Office, Type B	EA	1	1	1
539.191	Remove and Reset Field Office	LS	1		1
645.109	Remove and Reset Sign	EA	5	7	12
552.312	Type III Barricades	EA	1	1	2
52.33	Drum	EA	55	55	110
52.34	Cone	EA	55	55	110
552.35	Construction Signs	SF	139.0	139.0	278
552.361	Maintenance of Traffic Control Devices	LS	0.5	0.5	1
552.38	Flaggers	HR	100	100	200
552.41	Portable Changeable Message Sign	EA	1	1	2
55.101	#6 AWG Wire	LF	1170	860	2,030
555.11	#10 AWG Wire	LF	590	430	1,020
556.50	Baled Hay, in place	EA	5	5	10
56.632	30 Inch Temporary Silt Fence	LF	370	450	820
559.10	Mobilization	LS	0.5	0.5	1
300.01	Removal of Underground Tanks - Gas and Diesel (SB Plaza)	LS	1	1	1
300.02	Removal of Underground Tanks - Gas and Diesel (NB Plaza)	LS	1		1
300.03	Underground Tank Installation - Gas and Diesel (SB Plaza)	LS	_	1	1
300.04	Underground Tank Installation Gas and Diesel (NB Plaza)	LS	1	_	1
00.05	Aboveground Diesel Tank Installation (SB Plaza)	LS		1	1
00.06	Aboveground Diesel Tank Installation (NB Plaza)	LS	1		1
300.07	Aboveground Gas Tank Installation (SB Plaza)	LS		1	1
300.08	Aboveground Gas Tank Installation (NB Plaza)	LS	1		1
300.20	Canopy Demolition - Gas and Diesel (SB Plaza)	LS		1	1
300.21	Canopy Demolition - Gas and Diesel (NB Plaza)	LS	1		1
300.50	New Canopy Installation - Gas and Diesel (SB Plaza)	LS	1	1	1
800.51	New Canopy Installation - Gas and Diesel (NB Plaza)	LS	1	1	1

ntities.d	
Qua	0,
mate	

ie Quanti	Scale	e:			Designed by								
0X_Estimat	No.	Revision	Ву	Date				ITB			HNTB CORPORATION 340 County Road, Suite 6-C Westbrook, ME 04092 TEL (207) 774-5155	MAINE TURNPIKE	THE GOLD STAR MEMORIAL HIGHWAY
0					CONSULTANT	PROJECT	MANAGER	Dale A. Mitchel	I, P.E.		FAX (207) 228-0909	$ \setminus \mathbf{X} / $	
me						By	Date		By	Date			
enc					Designed	PEM	7\18	Checked	LZD	7\18			
Ē					Drawn	SLS	7\18	In Charge of	RAL	7\18		MTA PROJECT MAN	AGER: Peter S. Merfeld, P.E.

KENNEBUNK TRAVEL PLAZAS FUEL SYSTEM REPLACEMENT MILE 25.5 SB AND NB

ESTIMATED QUANTITIES

CONTRACT:2018.18

SHEET NUMBER: EQ-01

GENERAL

I. ALL WORK SHALL CONFORM TO THE MAINE DEPARTMENT OF TRANSPORTATION (MAINEDOT) STANDARD DETAILS FOR HIGHWAYS AND BRIDGES (LATEST REVISION, THE MAINEDOT BEST MANAGEMENT PRACTICES FOR EROSION AND SEDIMENT CONTROL (LATEST REVISION) AND THE 2014 MAINEDOT STANDARD SPECIFICATIONS, EXCEPT AS MODIFIED BY THE MAINE TURNPIKE'S SUPPLEMENTAL SPECIFICATIONS AND SPECIAL PROVISIONS UNLESS OTHERWISE INCLUDED IN THESE PLANS.

2. THE CONTRACTOR SHALL SUBMIT THE PROPOSED STAGING AREA(S) AND FIELD TRAILER LOCATION TO THE RESIDENT FOR APPROVAL PRIOR TO STARTING WORK

3. ANY DAMAGE TO FINAL PAVEMENT, SLOPES, OR STRUCTURES CAUSED BY THE CONTRACTOR'S EQUIPMENT, PERSONNEL OR OPERATIONS SHALL BE REPAIRED TO THE SATISFACTION OF THE RESIDENT, ALL WORK, EQUIPMENT, AND MATERIALS REQUIRED TO MAKE REPAIRS SHALL BE AT THE CONTRACTOR'S EXPENSE.

4. PROJECT BENCHMARK:

POINT #902 - TBM ON SE CORNER OF CONCRETE PAD NORTHING: 2/0266.743 FASTING. 2847815 408 FI EVATION: 112.067

POINT #1549 - TBM SET ON NW CORNER OF LIGHT POLE A36 NORTHING: 211041,219 EASTING: 2848680.720 ELEVATION: 99.506'

5. AS-BUILT PLANS FOR THE SERVICE PLAZAS AND EXISTING FUEL SYSTEM ARE AVAILABLE FROM THE AUTHORITY UPON REQUEST.

6 CONTRACTOR IS RESPONSIBLE FOR THE FINAL DESIGN OF ALL FUEL SYSTEM AND FUEL SYSTEM RELATED ITEMS UNLESS OTHERWISE NOTED IN THE PLANS OR SPECIFICATIONS. CONTRACTOR SHALL SUBMIT FINAL P.E. STAMPED DRAWINGS FOR REVIEW AND APPROVAL PRIOR TO CONSTRUCTION OR AS NOTED IN THE PLANS AND SPECIFICATIONS.

7. CONTRACTOR TO PROVIDE, FOR APPROVAL, LAYOUT PLAN AND DETAILS FOR TEMPORARY POWER AND COMMUNICATION TO TEMPORARY FUEL SYSTEM AND KIOSKS.

<u>LIGHTING</u>

I. EXISTING LIGHTING WITHIN THE PROJECT LIMITS SHALL BE OPERATIONAL AT ALL TIMES UNLESS NOTED OTHERWISE ON THE PLANS.

2. ALL ENCOUNTERED WIRE SHALL BE CAREFULLY CROSSED. NO SPLICES ALLOWED IN LINE. ONLY IN JUNCTION BOXES

3. EXISTING CONDUIT MAY BE ASBESTOS CEMENT CONDUIT. CONTRACTOR SHALL TAKE EXTREME CARE NOT TO DAMAGE IT. ALL EXISTING CONDUIT THAT REQUIRES REMOVAL DUE TO NEW CONSTRUCTION SHALL BE REMOVED PER THE SPECIFICATIONS, SPECIAL PROVISION 105.2 AND AS DIRECTED BY THE RESIDENT.

4. ALL WIRE SHALL BE COPPER, NO ALUMINUM WIRE IS ALLOWED.

5. ALL LIGHT STANDARD AND CONDUIT TRENCHES SHALL BE INSTALLED IN A MANNER THAT AVOIDS DRAINAGE STRUCTURES AND UTILITIES

6. PROPOSED NON-METALLIC CONDUIT SHALL BE 2" SCHEDULE 80 PVC AND CONTAIN TWO (2) *6 AND ONE (1) *10 (GROUND) WIRES CONSISTENT WITH EXISTING CIRCUIT. CONTRACTOR TO FIELD VERIFY.

7. LIGHTING CONDUIT, JUNCTION BOXES, AND WIRE SHALL BE PAID FOR UNDER THE APPROPRIATE PAY ITEMS

EARTHWORK

I. WASTE MATERIALS SHALL BE DISPOSED OF OFF THE PROJECT SITE. IN ACCORDANCE WITH CHAPTER 404, DEPARTMENT OF ENVIRONMENTAL PROTECTION SOLID WASTE MANAGEMENT RULES.

2. EXCAVATIONS ACCOMPLISHED AS PART OF THIS PROJECT SHALL BE CONSTRUCTED IN ACCORDANCE WITH OSHA SUBPART P OF 29 CFR PART 1926.650-652 (CONSTRUCTION STANDARDS FOR EXCAVATION).

3. COMMON BORROW SHALL BE COMPACTED TO 90% OF ITS MAXIMUM DRY AGREGATE SHALL BE COMPACTED TO 95% OF THEIR MAXIMUM DRY DENSITY AS DETERMINED BY THE MODIFIED PROCTOR.

EROSION CONTROL

I. THE ANTICIPATED EROSION CONTROL DEVICES ARE SHOWN ON THE PLANS. THE CONTRACTOR SHALL PROPOSE ACTUAL TYPE AND LOCATION OF DEVICES FOR APPROVAL BY THE RESIDENT. ADDITIONAL MEASURES MAY BE PROPOSED BY THE CONTRACTOR DUE TO SITE OR WEATHER CONDITIONS. THE RESIDENT MAY DIRECT THE CONTRACTOR TO IMPLEMENT ADDITIONAL MEASURES. ANY ADDITIONAL MEASURES APPROVED BY THE RESIDENT WILL BE MEASURED FOR PAYMENT

2. 4" LOAM HAS BEEN ESTIMATED FOR 100% OF THE DISTURBED SLOPE AREA. ACTUAL PLACEMENT OF THE LOAM SHALL BE AS DESIGNATED BY THE RESIDENT

3. UNLESS OTHERWISE NOTED. SEEDING METHOD NO. / SHALL BE UTILIZED ON ALL LAWNS AND DEVELOPED AREAS: SEEDING METHOD NO. 2 SHALL BE UTILIZED ON ALL OTHER AREAS

4. MULCH SHALL BE APPLIED IN AREAS SEEDED EXCEPT WHERE EROSION CONTROL BLANKET IS SPECIFIED.

5. ALL TEMPORARY AND PERMANENT EROSION CONTROL DEVICES SHALL BE INSTALLED IN ACCORDANCE WITH THE MAINE ENVIRONMENTAL PROTECTION BEST MANAGEMENT PRACTICES.

6. TEMPORARY SEED SHALL BE APPLIED TO ALL DISTURBED AREAS THAT WILL NOT BE SEEDED WITH FINAL SEED WITHIN 30 DAYS.

7. TEMPORARY STABILIZATION WITH MULCH OR OTHER NON-ERODABLE COVER IS REQUIRED ON ALL EXPOSED SOILS THAT WILL NOT BE WORKED ON FOR MORE THAN 7 DAYS. AREAS WITHIN 75 FEET OF A WETLAND OR WATERBODY SHALL BE STABILIZED WITHIN 48 HOURS OF THE INITIAL DISTURBANCE OF THE SOIL OR PRIOR TO ANY STORM EVENT, WHICHEVER COMES FIRST.

8. TEMPORARY EROSION CONTROL BLANKET, ITEM 613.319 SHALL BE INSTALLED IN ALL DITCHES AND SLOPES 2.1 AND STEEPER FROM THE TOP TO TOE OF SLOPE. LOAM AND SEED SHALL BE PLACED PRIOR TO THE INSTALLATION OF THE EROSION CONTROL BLANKET. LIMITS OF THE EROSION CONTROL BLANKET IN DITCHES SHALL BE 6'WIDE UNLESS OTHERWISE SPECIFIED ON THE PLANS OR AS DESIGNATED BY THE RESIDENT.

DRAINAGE

I. NO EXISTING DRAINAGE SHALL BE ABANDONED, REMOVED OR PLUGGED WITHOUT PRIOR APPROVAL OF THE RESIDENT.

2. INLETS AND OUTLETS OF ALL CULVERTS SHALL BE RIPRAPPED UNLESS OTHERWISE NOTED ON THE PLANS OR DIRECTED BY THE RESIDENT.

3. IF FOUNDATION MATERIAL IS REQUIRED UNDER CULVERTS, IT SHALL MEET THE REQUIREMENTS FOR GRANULAR BORROW - UNDERWATER BACKFILL.

4. ANY NECESSARY CUTTING OF EXISTING CATCH BASINS TO TAKE A PROPOSED PIPE WILL NOT BE PAID FOR SEPARATELY AND SHALL BE INCIDENTAL TO THE PROPOSED CULVERT ITEMS.

5. ANY NECESSARY CUTTING OF EXISTING PIPES TO FIT IN AREAS OF PROPOSED CATCH BASINS WILL NOT BE PAID FOR SEPARATELY AND SHALL BE INCIDENTAL TO THE PROPOSED CATCH BASIN ITEMS.

6. EXISTING CULVERTS TO REMAIN SHALL BE CLEANED AS DIRECTED BY THE RESIDENT. PAYMENT WILL BE MADE UNDER ITEM 604.182 CLEANING EXISTING CATCH BASIN AND MANHOLE.

UTILITIES

I. EXISTING UTILITIES ON THESE PLANS WERE COMPILED FROM FIELD SURVEY AND VARIOUS OTHER SOURCES. LOCATIONS ARE NOT GUARANTEED TO BE ACCURATE NOR IS IT GUARANTEED THAT ALL UTILITIES ARE SHOWN. NO SEPARATE OR ADDITIONAL COMPENSATION WILL BE ALLOWED TO THE CONTRACTOR DUE TO ANY VARIANCE BETWEEN THE DATA SHOWN ON THE PLANS AND THE ACTUAL FIELD CONDITIONS ENCOUNTERED. NO WORK SHALL BE STARTED UNTIL THE OWNERS OF THE VARIOUS UTILITIES ARE NOTIFIED BY THE CONTRACTOR OF THE PROPOSED CONSTRUCTION. THE CONTRACTOR IS ALSO REQUIRED TO CALL DIG SAFE AT I-888-344-7233 PRIOR TO THE START OF THE WORK. THE CONTRACTOR SHALL NOTIFY THE RESIDENT IO DAYS PRIOR TO CONSTRUCTION SO THE RESIDENT MAY COORDINATE WITH DIG SMART.

2. ALL UTILITY FACILITIES SHALL BE ADJUSTED BY THE RESPECTIVE UTILITIES UNLESS NOTED OTHERWISE.

3. THE UTILITIES INVOLVED IN THIS CONTRACT ARE: GREG HINDS, THE MAINE TURNPIKE AUTHORITY KENNEBUNK LIGHT & POWER DISTRICT KENNEBUNK, KENNEBUNKPORT, AND WELLS WATER DISTRICT KENNEBUNK SEWER DISTRICT SPECTRUM UNITI

4. THERE IS AN EXISTING SOIL VAPOR MONITORING SYSTEM INCLUDING PIPING NETWORKS AND MONITORING WELLS AROUND THE EXISTING UNDERGROUND STORAGE TANKS AND DIESEL DISPENSERS. THIS MONITORING SYSTEM IS ABANDONED AND SHALL BE PROPERLY DISPOSED OF IF ENCOUNTERED DURING EXCAVATION. PAYMENT FOR THIS WORK SHALL BE INCIDENTAL TO TANK REMOVALS.


lotes.dç	Scale	:		Designed b	y:							
00X_General	No.	Revision	By Date	-		HN	ITB			HNTB CORPORATION 340 County Road, Suite 6-C Westbrook, ME 04092	MAINE TURNPIKE	THE GOLD STAR MEMORIAL HIGHWAY
0				CONSULTANT	PROJEC	T MANAGER:	Dale A. Mitche	I, P.E.		TEL (207) 774-5155 FAX (207) 228-0909		
ĒΙ					By	Date		By	Date			
ena				Designed	CDH	7\18	Checked	LZD	7\18]		
Filen				Drawn	CDH	7\18	In Charge of	RAL	7\18		MTA PROJECT MANA	AGER: Peter S. Merfeld, P.E.


KENNEBUNK TRAVEL PLAZAS FUEL SYSTEM REPLACEMENT MILE 25.5 SB AND NB


GENERAL NOTES

CONTRACT:2018.18

SHEET NUMBER: GN-01







Drawn

CONTRACT:2018.18

SHEET NUMBER: MD-01

KENNEBUNK TRAVEL PLAZAS FUEL SYSTEM REPLACEMENT MILE 25.5 SB AND NB

DRAINAGE DETAILS


2. PAYMENT FOR CANOPY DRAINAGE SHALL BE INCIDENTAL TO NEW CANOPY INSTALLATION - GAS AND DIESEL.


CANOPY DRAINAGE NOTES: I.FOR MORE INFORMATION ON FOOTING, PAVEMENT SLAB, RAISED ISLAND AND ISLAND SLAB SEE STRUCTURAL DETAIL SHEETS SOI-SO4


- CONCRETE ISLAND SLAB - PAVEMENT SLAB

EXCAVATION IF ENCOUNTERED 0 DETECTABLE WARNING TAPE -6" MIN. ALL AROUND NOTES:

PAY LIMIT OF SPECIAL







UNPAVED AREAS

18" MIN.

4" LOAM & SEED -

DETECTABLE WARNING TAPE

1∕2 OD PLUS 6"

½ OD PLUS 6

PROPOSED CONDUIT -

NOTES:

DIRECTED BY THE RESIDENT.

ō,

PAVED AREAS

 \bigcirc

⅓ ID PIPE

+ 1.5 FT (MIN 3 FT) STANDARD PIPE/CONDUIT TRENCH DETAIL N.T.S.

I. BEDDING SHALL BE COMPACTED TO A MINIMUM 95% STANDARD PROCTOR DENSITY. USE HAND TAMPERS OR VIBRATORY COMPACTORS.

2. CONTRACTOR SHALL SHORE TRENCH SIDES WHEN REQUIRED OR AS

18"

MIN.

BIT. CONC. AND BASE COURSES

FULL DEPTH BIT. SAWCUT

AT EXIST. PAVEMENT

_DENSELY COMPACTED SAND INSTALL AND COMPACT IN 6" LAYERS

BACKFILL WITH BEDDING MATERIAL.


FIRM SUBGRADE, OR COMPACTED BACKFILL

REMOVE UNSUITABLE MATERIAL AS DIRECTED,


SUITABLE BACKFILL

MATERIAL

AS SPECIFIED. REFER TO PARKING TYPICAL SECTION








DIMENSIONS FOR SLOPE OF 2:1

ate:7/9/2018

							STONE	STONE
D	a	b	с	е	f	g	DEPTH	(CY)
	(FT)	(FT)	(FT)	(FT)	(FT)	(FT)	(FT)	
12"	1.00	4.00	3.00	2.00	6.00	1.00	1.50	1.30
15"	1.00	4.50	3.37	2.25	6.75	1.63	1.50	1.70
18"	1.00	5.00	3.75	2.50	7.50	2.25	1.50	2.09
21"	1.00	5.50	4.13	2.75	8.25	2.88	1.50	2.58
24"	1.00	6.00	4.50	3.00	9.00	3.50	1.50	3.12
30"	1.00	7.00	5.25	3.50	10.50	4.75	1.50	4.33
36"	1.00	8.00	6.00	4.00	12.00	6.00	1.50	5.75
42"	1.00	9.00	6.75	4.50	13.50	7.25	1.50	7.37
48"	1.00	10.00	7.50	5.00	15.00	8.50	1.50	9.18
54"	1.00	11.00	8.25	5.50	16.50	9.75	1.50	11.19
60"	1.00	12.00	9.00	6.00	18.00	11.00	1.50	13.40
66"	1.00	13.00	9.75	6.50	19.50	12.25	1.50	15.81
72"	1.00	14.00	10.50	7.00	21.00	13.50	1.50	18.41
84"	1.00	16.00	12.00	8.00	24.00	16.00	1.50	24.22



DIMENSIONS FOR SLOPE OF 4:1

							STONE	STONE
D	a	b	с	e	f	g	DEPTH	(CY)
	(FT)	(FT)	(FT)	(FT)	(FT)	(FT)	(FT)	
12"	1.00	8.00	6.00	2.00	6.00	0.00	1.50	2.20
15"	1.00	9.00	6.75	2.25	6.75	0.00	1.50	2.80
18"	1.00	10.00	7.50	2.50	7.50	0.00	1.50	3.40
21"	1.00	11.00	8.25	2.75	8.25	0.00	1.50	4.10
24"	1.00	12.00	9.00	3.00	9.00	0.00	1.50	4.86
30"	1.00	14.00	10.50	3.50	10.50	0.00	1.50	6.58
36"	1.00	16.00	12.00	4.00	12.00	0.00	1.50	8.56
42"	1.00	18.00	13.50	4.50	13.50	0.50	1.50	10.92
48"	1.00	20.00	15.00	5.00	15.00	1.00	1.50	13.57
54"	1.00	22.00	16.50	5.50	16.50	1.50	1.50	16.50
60"	1.00	24.00	18.00	6.00	18.00	2.00	1.50	19.72
66"	1.00	26.00	19.50	6.50	19.50	2.50	1.50	23.22
72"	1.00	28.00	21.00	7.00	21.00	3.00	1.50	27.01
84"	1.00	32.00	24.00	8.00	24.00	4.00	1.50	35.45

DIMENSIONS FOR SLOPE OF 6:


							STONE	STONE
D	a	b	с	e	f	g	DEPTH	(CY)
	(FT)	(FT)	(FT)	(FT)	(FT)	(FT)	(FT)	
12"	0.50	9.00	7.50	1.50	4.50	0.00	1.50	2.30
15"	0.50	10.50	8.75	1.75	5.50	0.00	1.50	2.93
18"	0.50	12.00	10.00	2.00	6.50	0.00	1.50	3.57
21"	0.50	13.50	11.25	2.25	7.25	0.00	1.50	4.46
24"	0.50	15.00	12.50	2.50	8.00	0.00	1.50	5.44
30"	0.50	18.00	15.00	3.00	9.50	0.00	1.50	7.71
36"	0.50	21.00	17.50	3.50	11.00	0.00	1.50	10.37
42"	0.50	24.00	20.00	4.00	12.50	0.00	1.50	13.42
48"	0.50	27.00	22.50	4.50	14.00	0.00	1.50	16.87
54"	0.50	30.00	25.00	5.00	15.50	0.00	1.50	20.70
60"	0.50	33.00	27.50	5.50	17.00	0.00	1.50	24.93
66"	0.50	36.00	30.00	6.00	18.50	0.00	1.50	29.55
72"	0.50	39.00	32.50	6.50	20.00	0.00	1.50	34.56
84"	0.50	45.00	37.50	7.50	23.00	0.00	1.50	45.76

trol Detail.dgn

olDet											2. STONE QUANTITIES ARE FO	R ONE END OF THE F	PIPE.
ontro	Scale:				Designed by	y:							
osion C								ITB			HNTB CORPORATION	MAINE TURNPIKE	-
DX_Er	No.	Revision	By	Date	1						340 County Road, Suite 6-C Westbrook, ME 04092 TEL (207) 774-5155		ME
ŏ					CONSULTANT	PROJEC	CT MANAGER:	Dale A. Mitchel	I, P.E.		FAX (207) 228-0909		
me						By	Date		By	Date			
enc					Designed	PEM	7\18	Checked	LZD	7\18			
Ē					Drawn	2 12	7\18	In Charge of	RAI	7\18		MTA PROJECT MANA	GER: Pete

18" PLAIN RIPRAP 1:1 FOR 4:1 1:1 FOR 6:1 1/2 :1 FOR 2:

<u>SECTION B-B</u>



ROADWAY CULVERT END SLOPE TREATMENT

<u>NOTES:</u>

- 1. THE DIMENSIONS SHOWN ARE APPROXIMATE AND MAY BE MODIFIED BY THE RESIDENT.
 - THE GOLD STAR MEMORIAL HIGHWAY


MTA PROJECT MANAGER: Peter S. Merfeld, P.E.

KENNEBUNK TRAVEL PLAZAS FUEL SYSTEM REPLACEMENT MILE 25.5 SB AND NB


EROSION CONTROL DETAILS


CONTRACT:2018.18

SHEET NUMBER: EC-01




PHASE I SEQUENCE OF CONSTRUCTION: REMOVE CURBED ISLAND FROM STA. 218+25 TO STA. 220+40. PLACE GRAVEL AND 3* HMA. 2. INSTALL TEMPORARY: LIGHTING AND TEMPORARY CONCRETE BARRIER. 3. INSTALL C.N. BROWN PROVIDED TEMPORARY KIOSK 4. INSTALL TEMPORARY GAS ABOVEGROUND STORAGE TANKS AND DISPENSERS AND MAKE COMPLETELY FUNCTIONAL BEFORE CLOSING EXISTING DISPENSERS; THIS INCLUDES POWER, COMMUNICATIONS, AND POINT OF SALE. 5. INSTALL TEMPORARY ACCESS RAMP. 6. COVER TRUCK PARKING STALLS WITH BLACK TAPE, INSTALL TEMPORARY NO PARKING SIGNS. 7. INSTALL TEMPORARY DIESEL ABOVEGROUND STORAGE TANK AND DISPENSERS AND MAKE COMPLETELY OPERATIONAL BEFORE CLOSING EXISTING DISPENSERS. 8. INSTALL OIL WATER SEPARATOR SYSTEM AND DRAINAGE PIPES AND MANHOLES. <u>LEGEND</u> WORK AREA - PHASE I TEMPORARY PAVEMENT 6' CHAIN LINK SAFETY FENCE 222 ± 00 223+00 0 0 0 0 0 0 0 0 0 0 0 CUZ, TEMPORARY CONCRETE 2" CMP 18" CMP (APPROXIMATE LOCATION) KENNEBUNK TRAVEL PLAZAS FUEL SYSTEM REPLACEMENT MILE 25.5 SB AND NB MAINTENANCE OF TRAFFIC PHASE 1 - SOUTHBOUND PLAZA SHEET NUMBER: MOT-01 CONTRACT:2018.18 10 OF 43







<u>NOTE:</u> I.CONTRACTOR SHALL MAKE ACCOMMODATIONS FOR SCHEDULED SERVICE PLAZA AND FUEL STATION DELIVERIES.





AUTHORIZED VEHICLES ONLY" ED ON TYPE III BARRICADE
NS (TYP.) CE-@ 10' O.C.)
 PHASE 2 SEQUENCE OF CONSTRUCTION: EXCAVATE, AND_REMOVE_EXISTING, UNDERGROUND, FUEL_AND-DIESELE TANKS. INSTALL NEW TANKS. REMOVE EXISTING FUEL AND DIESEL SLABS, DISPENSERS AND CANOPY AND INSTALL NEW SLABS, DISPENSERS, AND CANOPY. NEW DISPENSERS AND CONSTALL NEW SLABS, DISPENSERS, AND CANOPY. NEW DISPENSERS
SHALL BE FULLY OPERATIONAL BEFORE REMOVING THE TEMPORARY DISPENSERS.CONTRACTOR SHALL COORDINATE WITH RESIDENT AND C.N. BROWN FOR REMOVAL AND INSTALLATION OF DISPENSER.C.N. BROWN WILL TAKE DELIVERY OF DISPENSERS, STORE THEM, AND PROVIDE NEW/REFURBISHED DISPENSERS FOR INSTALLATION.
3. INSTALL DRAINAGE PIPES AND CATCH BASINS WHERE POSSIBLE.CATCH BASINS NOT TO RECEIVE WATER UNTIL REMAINING SYSTEM IS INSTALLED IN PHASE III.
4. GRADE AS SHOWN ON THE PLANS.
5. INSTALL CURBED ISLANDS AND PROPOSED SIDEWALK.
LEGEND
WORK AREA - PHASE 2
TEMPORARY PAVEMENT
TRAVEL PLAZA BUILDING 6' CHAIN LINK SAFETY FENCE
EXISTING DISPENSERS 6' CHAIN LINK SAFETY FENCE (INSTALL 8' (TYP.)
ISLAND 15LAND
-TEMPORARY CONCRETE BARRIER (TYP.) (APPROXIMATE LOCATION)
KENNEBUNK TRAVEL PLAZAS FUEL SYSTEM REPLACEMENT MILE 25.5 SB AND NB MAINTENANCE OF TRAFFIC
PHASE 2 - SOUTHBOUND PLAZA
SHEET NUMBER: MOT-04CONTRACT:2018.1813 OF 43




A DE EXT	\$37 \$37
	FWELD
18 10P	
	80 at 66
/ ///	Y2" APPLE
122/02	
CONSTRUCTION B.L.	133+00 L
ITEM 607.018 6" CHAIN LINK SAFETY FE	NCE
STA. 127+15, 44' RT. TO STA. 127+33 STA. 128+15, 260' RT. TO STA. 127+5	• 76' LT. 122
STA: 127+52, 170' RT. TO STA, 127+1	5, 44 ⁴ RT. 162
//////////////////////////////////	
LEGEND	
	WORK AREA - PHASE 2
	TEMPORARY PAVEMENT
· · · · · · · · · · · · · · · · · · ·	6' CHAIN LINK SAFETY FENCE
ASE 2 SEQUENCE OF CONSTRU	
XCAVATE AND REMOVE EXISTING FUEL AND DIES EW TANKS	EL IANKS. INSTALL
EMOVE EXISTING FUEL AND DIESEL SLABS, DISPE ND INSTALL NEW SLABS, DISPENSERS, AND CANOP)	Y.NEW DISPENSERS
HALL BE FULLY OPERATIONAL BEFORE REMOVING ISPENSERS.CONTRACTOR SHALL COORDINATE WITH ROWN FOR REMOVAL AND INSTALLATION OF DISPE	RESIDENT AND C.N.
ROWN FOR REMOVAL AND INSTALLATION OF DISPE AKE DELIVERY OF DISPENSERS,STORE THEM,AND EW/REFURBISHED DISPENSERS FOR INSTALLATIO	PROVIDE
ISTALL DRAINAGE PIPES AND CATCH BASINS WHE	ERE POSSIBLE.CATCH
ASINS NOT TO RECEIVE WATER UNTIL REMAINING ISTALLED IN PHASE III.	SYSTEM IS
RADE AS SHOWN ON THE PLANS.	
NSTALL CURBED ISLAND, AS MUCH AS POSSIBLE.	
<u>E:</u> TRACTOR SHALL MAKE ACCOMMODATIONS FO	R SCHEDULED SERVICE PLAZA AND FUEL
ION DELIVERIES.	, SOMEDOLLD SERVICE I LALA AND I ULL
1	
KENNEBUNK TRAVEL F	PLAZAS FUEL SYSTEM
	E 25.5 SB AND NB
MAINTENANCE	of traffic
PHASE 2 - NOR	
CONTRACT:2018.18	SHEET NUMBER: MOT-05 14 OF 43









IDENTIFI-		E OF IGN		TEXT DI	MENSIONS	(INCHES)	NUMBER OF	COL	OR	AREA II
CATION NUMBER	WIDTH	HEIGHT	ΤΕΧΤ	LETTER HEIGHT	VERTICAL SPACING	ARROW RTE.MKR.	SIGNS REQUIRED	BACK- GROUND	LEGEND BORDER	SQUARE FEET
CS-I	54"	18"	GAS & EXIT ↑ PLAZA SERVICES →	4"C 4"C	3" 4" 3"	4"x6" 4"X6"	2	ORANGE	BLACK	6.75 (13.50)
CS-2	54"	<i>\8</i> "	PLAZA SERVICES GAS	4"C 4"C	3.5" 3" 3.5"	4"x6"	1			6.75 (6.75)
CS-3	42"	24"	NO RETURN To parking Get gas last	4"C 4"C 4"C	3" 3" 3" 3"		/			7.00 (7.00)
CS-4	24"	18"	EXIT 1 GAS 🖈	4"C 4"C	3" 4" 3"	4"x6" 4"X6"	2			3.00 (6.00)
CS-5	54"	<i>\8</i> "	PLAZA SERVICES → CARS ONLY	4"C 4"C	3.5" 3" 3.5"	<i>4"x6"</i>	/			6.75 (6.75)
CS-6	54"	18"	PLAZA SERVICES Cars only	4"C 4"C	3.5" 3" 3.5"	4"x6"	/			6.75 (6.75)
CS-8	48"	36"	DIESEL FUEL † No additional Parking or Plaza services	4"C 4"C 4"C 4"C	6" 3" 3" 5"	4"x6"	/			12.00 (12.00)
CS-II	36"	30"	NO RETURN TO PARKING NO EXIT TO KENNEBUNK	4"C 4"C 4"C 4"C 4"C	2.5" 3" 3" 2.5"		/			7.50 (7.50)
CS-14	<i>\8</i> "	<i>\8</i> "	IN PLAZA	4"C 4"C	3.5" 3" 3.5"		4			2.25 (9.00)
CS-15	48"	36"	♥ DIESEL FUEL NO ADDITIONAL PARKING OR PLAZA SERVICES	4"C 4"C 4"C 4"C	6" 3" 3" 5"	4"x6"	1			12.00 (12.00)
CS-16	54"	18"	PLAZA SERVICES GAS	4"C 4"C	3.5" 3" 3.5"	4"x6"	/			6.75 (6.75)
CS-17	54"	18"	+ PLAZA SERVICES GAS	4"C 4"C	3.5" 3" 3.5"	4"x6"	/			6.75 (6.75)
CS-18	48"	12"	ΝΟ	8"D	2" 2"		2			4.00 (8.00)

CONSTRUCTION SIGN SUMMARY


IDENTIFI-		E OF GN		TEXT	DIME	ENSIONS	(INCHES	NUMBER OF	COLO	AREA IN	
CATION NUMBER	WIDTH	HEIGHT	TEXT	TEXT LETTER VERTICAL ARROW HEIGHT SPACING RTE. MKR.F		SIGNS	BACK- GROUND	LEGEND BORDER	SQUARE FEET		
CS-19	36"	36"	FULL SERVICE ONLY	6"D 6"D 6"D		5" 4" 4" 5"		4	BLUE	WHITE	9.00 (36.00)
R5-11	36"	24"	AUTHORIZED VEHICLES ONLY	(STAN	CONFO IDARD 94 ED.	MENSIONS ORM TO O HIGHW, MITION AI PPLEMEN	THE AY SIGNS ND 2012	2	WHITE	BLACK	6.00 (12.00)
R8-3	<i> 8</i> "	24"	N O PARKING					10	WHITE	RED	3.00 (30.00)
G20-2	36"	<i>\8</i> "	END Road Work					6	ORANGE	BLACK	4.50 (27.00)
W20-I	48"	<i>48</i> "	ROAD WORK AHEAD					4	ORANGE	BLACK	16.00 (64.00)
W20-1	48"	48"	< WORK >			V		4	ORANGE	BLACK	


dgr


0ate:7/9/2018

Summary_1	Scale:	NOT TO SCALE		Designed by:					HNTB CORPORATION	MAINE	
00X_Sign	No.	Revision	By Dat			NTB			340 County Road, Suite 6-C Westbrook, ME 04092 TEL (207) 774-5155	TURNPIKE	THE GOLD STAR MEMORIAL HIGHWAY
ename: (CONSULTANT PROJE By Designed MHF	Date	Checked	ell, P.E. By JRH	Date 7\18	FAX (207) 228-0909		
File				Drawn SLS	7\18	In Charge of	RAL	7\18		MTA PROJECT MANA	AGER: Peter S. Merfeld, P.E.

KENNEBUNK TRAVEL PLAZAS FUEL SYSTEM REPLACEMENT MILE 25.5 SB AND NB MAINTENANCE OF TRAFFIC SIGN SUMMARY SHEET NUMBER: SS-01











PROFILE SOUTHBOUND APPROACH RAMP TO PROPOSED DIESEL/TRUCK FUELING WILL MATCH EXISTING PROFILE


KENNEBUNK TRAVEL PLAZAS FUEL SYSTEM REPLACEMENT MILE 25.5 SB AND NB











MTA PROJECT MANAGER: Peter S. Merfeld, P.E.

NOTES:

I. ALL ELEMENT SIZES AND LAYOUT ARE FOR INFORMATION ONLY. CANOPY SHALL BE DESIGNED BY THE CONTRACTOR IN ACCORDANCE WITH SP800.

2. CANOPY LAYOUT AND DETAILS SHALL BE CONSISTENT WITH DETAILS OF THE DISPENSER SLABS SHOWN ON SHEETS S-02 AND S-03.

3. ALL STRUCTURAL STEEL SHALL BE AS FOLLOWS: -W SHAPES: ASTM A992


- HOLLOW STRUCTURAL SHAPES: ASTM A500 GRADE B
- PLATES: ASTM A572 GRADE 50
- FASTENERS: F3/25


4. ALL WELDING SHALL BE PERFORMED IN ACCORDANCE WITH AWS DI.I.

5. GAS DISPENSER CANOPY SHOWN, DIESEL DISPENSER CANOPY SIMILAR.

6. C.N. BROWN WILL PROVIDE CANOPY DECALS FOR FACTORY TO INSTALL. CONTRACTOR TO COORDINATE WITH RESIDENT AND CN BROWN ACCORDINGLY.

KENNEBUNK TRAVEL PLAZAS FUEL SYSTEM REPLACEMENT MILE 25.5 SB AND NB CANOPY PLAN AND ELEVATION SHEET NUMBER: S-01





MTA PROJECT MANAGER: Peter S. Merfeld, P.E.

Checked

In Charge of RAL

Designed

Drawn

JDW PEB

7\18

TRC


7\18

CONTRACT:2018.18

29 OF 43

REPLACEMENT MILE 25.5 SB AND NB PLAN - CONCRETE ISLAND 2 CANOPY COLUMN AND BUMPER DETAILS SHEET NUMBER: S-03

2. CANOPY COLUMN FOUNDATION IS SHOWN FOR INFORMATIONAL PURPOSES ONLY AND SHALL BE DESIGNED BY THE CANOPY SUPPLIER.



Drawn


MTA PROJECT MANAGER: Peter S. Merfeld, P.E.

CONTRACT:2018.18

30 OF 43

KENNEBUNK TRAVEL PLAZAS FUEL SYSTEM REPLACEMENT MILE 25.5 SB AND NB PLAN - CONCRETE SLAB AND ISLANDS AT DIESEL DISPENSERS SHEET NUMBER: S-04

NOTE FOR NOTES SEE SHEET S-02.




MTA PROJECT MANAGER: Peter S. Merfeld, P.E.

CONTRACT:2018.18


310F 43

KENNEBUNK TRAVEL PLAZAS FUEL SYSTEM REPLACEMENT MILE 25.5 SB AND NB PLAN - CONCRETE SLABS AT FUEL STORAGE TANKS SHEET NUMBER: S-05

1. FOR NOTES SEE SHEET S-02. 2. FOR REINFORCING SEE SHEET S-06.








NOTES 1. FOR NOTES SEE SHEET S-02. 2. FOR REINFORCING SEE SHEET S-08.


KENNEBUNK TRAVEL PLAZAS FUEL SYSTEM REPLACEMENT MILE 25.5 SB AND NB PLAN - CONCRETE SLAB AT FUEL STORAGE TANKS SHEET NUMBER: S-07

CONTRACT:2018.18

33 OF 43







MTA PROJECT MANAGER: Peter S. Merfeld, P.E.

Date 7∖18 7\18

CONSULTANT PROJECT MANAGER: Dale A. Mitchell, P.E. Date 7∖18

Checked

7\18 In Charge of RAL

By

TRC

By

JDW PEB

Designed

Drawn

- CONCRETE ISLAND



KENNEBUNK TRAVEL PLAZAS FUEL SYSTEM REPLACEMENT MILE 25.5 SB AND NB

SLAB DETAILS

CONTRACT:2018.18

SHEET NUMBER: S-09

		MARK	SITE	NO. LENGTH	TYPE	A	вс	D		MARK SIZ	E NO	LENGTH	TYPE	A	в	c	D		MARK	SITE	NO	ENGTH
		SB GASOLI	INE DISPEN	NSER SLAB	-					SB DIESEL DISPI	INSER S	LAB	Str	1		-		-	SB GASOLI GF501		SLAB	41'-3"
		G501 G502	5	90 39'-6" 82 11'-0"	Str Str					D502 5 D503 5	82	13'-6"	Str Str					-1	GF502 GF503	5	6	7'-2" 7'-10"
		G503 G504	5	82 22'-6" 72 3'-6"	Str Str					D503 5 D504 5 D505 5	16	5'-3"	Str					_	GF504	5	6	3'-8"
		G505 G506		12 5'-3" 10 7'-9"	Str Str					D506 5	144		Str Str					_	GF505 GF506	5	6	8'-8" 3'-5"
		G507 G508	5	37 8'-6" 8 3'-2"	Str Str					D507 5 D508 5	8	1'-2" 19'-0"	Str Str					_	GF507 GF508	5	6	1'-5" 5'-3"
		G509	5	4 3'-8"	Str					D509 5 D510 8			Str Str					_	GF509 GF510	5		31'-3" 5'-2"
		G510 G511	5	8 13'-4"	Str Str					D550 5			129	2'-6"	1'-0"	1'-0"			GF511 GF512	5	4	9'-9" 5'-8"
		G512 G513		8 12'-0" 44 2'-6"	Str Str					D551 5	8	5'-4"	138	1'-0"	1'-2" 3'-11"	1'-0" 0'-3"	0'-9" 1'-3"	_	GF513	5	4	11'-0"
		G514 G515	5	8 4'-4" 2 35'-0"	Str Str	-				D552 5 D553 5	32	3'-10	117 129	0'-3" 2'-6"	0'-8"	0'-3"	1-3	_	GF514 GF515	5 5	10	5'-9" 11'-3"
2018		G516 G517	5	2 34'-3" 2 32'-10"	Str Str					D554 5	-		118	3'-3"	0'-10"				GF516 GF520	5		40'-6" 8'-2"
/6//		G518	5	2 28'-0"	Str		_			NB DIESEL DISPI D501 5			Str	1		1	-	_	GF521	5	36	6'-4"
Date:7/9/2018		G519 G520	5	27 7'-6" 8 2'-8"	Str Str					D502 5 D503 5	82	13'-6"	Str Str			-	-	-	GF550	5	6 7	7'-11 1/2"
		G521 G522	5	2 7'-3" 2 6'-5"	Str Str					D504 5	16	5'-3"	Str						SB DIESEL			111.00
		G523	5	2 4'-9"	Str		_			D505 5 D506 5	144	3'-6"	Str Str	1				_	DF501 DF502	5		7'-2"
		G550 G551	5	8 4'-6" 8 5'-4"	129 138	2'-6" 1'-0"	1'-0" 1'-0" 1'-2" 1'-0"	0'-9"		D507 5 D508 5		1'-2" 19'-0"	Str Str						DF503 DF504	5		7'-10" 3'-8"
		G552 G553	5	2 16'-9" 16 4'-5"	117	2'-6"	11'-9" 2'-6" 3'-11" 0'-3"			D509 5 D510 8		18'-0" 2'-6"	Str Str	-				-	DF505 DF506	5		8'-8" 3'-5"
		G554	5	16 3'-10"	129	2'-6"	0'-8" 0'-8"	1-3		D550 5			129	2'-6"	1'-0"	1'-0"		_	DF507 DF508	5	2	1'-5" 5'-3"
		G555 G556	5	64 4'-1" 16 6'-6 3/4"			0'-10" '-6 3/4" 2'-6"	0'-6"		D551 5	8	5'-4"	138	1'-0"	1'-2"	1'-0"	0'-9"	_	DF509	5	2	31'-3"
		G556	5	32 2'-3 1/2"	117	0'-10"	1'-0" 0'-5 1/2	2" 0'-3 3/4"		D552 5 D553 5	32	3'-10	117 129	0'-3" 2'-6"	3'-11" 0'-8"	0'-3" 0'-8"	1'-3"	_	DF510 DF512	5 5	4	5'-2" 5'-8"
				NSER SLAB						D554 5	48	4'-1"	118	3'-3"	0'-10"				DF514 DF516	5		5'-9" 13'-10
		G501 G502		90 39'-6" 82 11'-0"	Str Str		-												DF520 DF521	5		8'-2" 6'-4"
		G503 G504		82 22'-6" 72 3'-6"	Str Str														DF550	5		7'-11 1/2"
		G505 G506	5	12 5'-3" 10 7'-9"	Str					<u>_</u>					+	-1						-11 1/2
		G507	5	37 8'-6"	Str Str														NB FUEL TA F501	ANK SLAE		41'-3"
		G508 G509	5	8 3'-2" 4 3'-8"	Str Str						\backslash								F502 F503	5		7'-2" 7'-10"
		G510 G511	5	4 4'-5" 8 13'-4"	Str Str					R=D	в				A				F504 f505	5	8	3'-8" 8'-8"
		G512 G513	5	8 12'-0" 44 2'-6"	Str Str														F506	5	8	3'-5"
		G514	5	8 4'-4"	Str										•	_			F507 F508	5 5	8	1'-5" 5'-3"
		G515 G516	5	2 35'-0" 2 34'-3"	Str Str					- ^ - ⁻						B			F509 F510	5		31'-3" 5'-2"
		G517 G518	5	2 32'-10" 2 28'-0"	Str Str														F511 F512	5		9'-9" 5'-8"
		G519 G520	5	27 7'-6" 8 2'-8"	Str Str					TYPE II7					ΤY	PE II	8		F513 F514	5 5		11'-0" 5'-9"
		G521 G522	5	2 7'-3" 2 6'-5"	Str Str	-				<u></u>							_		F515	5	15	11'-3"
		G523	5	2 4'-9"	Str														F516 GF520	5 5	16	53'-10" 8'-2"
		G550	5	8 4'-6"	129		1'-0" 1'-0"	01.01											GF521	5	48	6'-4"
		G551 G552	5	8 5'-4" 2 16'-9"	138 117	2'-6"	1'-2" 1'-0" 11'-9" 2'-6"	0'-9" 3'-9"											GF550	5	8 7	7'-11 1/2"
		G553 G554	5	16 4'-5" 16 3'-10"	117		3'-11" 0'-3" 0'-8" 0'-8"	1'-3														
		G555 G556		64 4'-1" 16 6'-6 3/4"	118 117		0'-10" '-6 3'4" 2'-6"	0'-6"		A	-				A		C	-				
		G556		32 2'-3 1/2"	117		1'-0" 0'-5 1/2							·								
											ÌT											
											В							D				
																		↓				
ے											Ľ											
e.dgr										<u>TYPE 129</u>					TY	PE 13	8					
Schedule.dgn															<u></u>	0						
	Scale:			Designed t	oy:										_							K
Reinforcing								5		HNTR	CORPO	RATION			MAINE		_			- -	-	n
Rein	No. Revision	R	By Date	-			NTE)		340 Count	v Roa	d. Suite 6	6-C		JRNPII			THE GO				
_X00										Westbro TEL (2	ok, ME 07) 71	04092 74-5155 28-0909	2		▲)	ME	MORIA	L HIG	iΗV	VAY	1
me: (CONSULTAN	F PROJEC	T MANAGI Date	ER: Dale A.M	litchell, P.E. By	Date	FAX (2	07) 22	28-0909			⋌							L
ilenar				Designed	JDW	7\18 7\18		TRC	7\18 7\18	1							ED. Date	r S Morfold D E				c
щΙ				Drawn	PEB	/ \10	In Charge	e of RAL	/ \10	1					FRUJEC	i manag	∍∟r. Pete	r S. Merfeld, P.E.				


GTH	TYPE	A	в	с	D
-3"	Str		-	<u>г</u>	
-2"	Str				
10"	Str				
-8"	Str				
8"	Str		-		
-8" -5"	Str	-			
-5"	Str				
2"	Str				
-3" '-3"					
-3	Str		_		
-2	Str		_		
-9"	Str				
-8"	Str				
'-0" -9"	Str				
-9"	Str				
-3"	Str		_		_
-6"	Str		_		_
-0	Str		_		
-4"	Str				
1/2"	Str	0'-9 1/2"	3'-7"	2'-6"	3'-7"
-3"	Str	1			-
-2"	Str				
10"	Str				
-8"	Str				
-8"	Str				
-5"	Str				
	Str				
-5"					
-3" '-3"	Str				
-2"	Str		_		
-2	Str		_		
-8"	Str	-		-	
-9"	Str				
-10	Str		_		
-2"	Str				
-4"	Str				
1/2"	Str	0'-9 1/2"	3'-7"	2'-6"	3'-7"
.3"	Str	<u>г</u> т	-		
-3" -2" 10"	Str				
10"	Str				
-8"	Str				
-8"	Str				
5"			-		
-5"	Str				
-5"	Str				
-3" '-3"	Str		_		
-3	Str				
-2" -9"	Str		_	┝──┤	
9	Str	-	_		
-8"	Str				
-0"	Str				
.9"	Str		_		
0.0	Str				
-3	Str				
-2"	Str	-	-		
-4"	Str				
1/2"			21 80		14.144
	Str	0'-9 1/2"	3'-7"	2'-6"	3'-7"

KENNEBUNK TRAVEL PLAZAS FUEL SYSTEM REPLACEMENT MILE 25.5 SB AND NB

REINFORCING SCHEDULE

CONTRACT:2018.18

SHEET NUMBER: S-10



<u>general note:</u>

- 1. TEMPORARY FUEL SYSTEM CONSISTS OF ABOVE GROUND FUEL STORAGE TANKS, DISPENSING EQUIPMENT, ITEMS AND COMPONENTS, THAT WILL BE USED TO MAINTAIN FUELING OPERATIONS WHILE FUEL SYSTEMS ARE BEING REPLACED. THE TEMPORARY FUEL SYSTEMS WILL BE OWNER FURNISHED EQUIPMENT. CONTRACTOR TO PROVIDE ELECTRICAL, COMMUNICATIONS, TEMPORARY LIGHTING, COMMISSIONING, AND FINAL INSTALLATION.
- 2. CONTRACTOR SHALL PROVIDE AND INSTALL TEMPORARY STRUCTURAL SUPPORTS FOR TANKS INCLUDING BOLLARDS.
- 3. MAKE SITE READY PRIOR TO INSTALLING THE OWNER FURNISHED EQUIPMENT. NO DEMOLITION OF THE EXISTING FUEL STORAGE AND DISPENSING SYSTEMS IS ALLOWED UNTIL THE TEMPORARY SYSTEMS ARE TESTED, COMMISSIONED AND OPERATIONAL.
- 4. CONTRACTOR SHALL COORDINATE WITH OWNER/ FUEL OPERATION TO CONNECT AND VERIFY POINT OF SALE OPERATIONS.
- 5 CONTRACTOR SHALL PROVIDE AND INSTALL TEMPORARY LIGHTING AT DISPENSERS.
- 6 CONTRACTOR SHALL PROVIDE THE FOLLOWING PER NFPA 30A FOR EACH TEMPORARY FUEL SYSTEM:
 A. AN EMERGENCY STOP BUTTON FOR THE PUBLIC AND THE STATION ATTENDANT.
 B. INCLUDE 2A 40BC FIRE EXTINGUISHERS AT
- B. INCLUDE 2A 40BC FIRE EXTINGUISHERS AT EACH DISPENSER.
 C. THE DISPENSERS THEMSELVES WILL BE
- C. THE DISPENSERS THEMSELVES WILL BE EQUIPPED WITH SHEAR VALVES IN CASE OF IMPAIRMENT.

KENNEBUNK TRAVEL PLAZAS FUEL SYSTEM REPLACEMENT MILE 25.5 SB AND NB SOUTHBOUND PLAZA SITE PLAN – TEMPORARY GAS/DIESEL SHEET NUMBER: M1


EB

ÊÐ

CONTRACT: 2018.18

EB

37 OF 43



GENERAL NOTE:

 DUE TO THE EXISTENCE OF THE FUELING SYSTEM, IT IS ANTICIPATED CONTAMINATED SOILS WILL BE ENCOUNTERED AS PART OF THIS PROJECT. PRIOR TO CONSTRUCTION, CONTRACTOR SHALL REFER TO 'PROCEDURE FOR THE MANAGEMENT OF CONTAMINATED MATERIALS ENCOUNTERED DURING CONSTRUCTION' DOCUMENTATION.

GENERAL ELECTRICAL NOTE:

- CONTRACTOR IS RESPONSIBLE FOR FIELD VERIFYING ALL EXISTING EQUIPMENT (CONDUIT RUNS, MATERIAL, ETC.) FOR LOCATIONS AND SIZES BEFORE BEGINNING WORK.
- KEY NOTES:
- (1) SERVICE ROOM HAS ELECTRICAL PANEL FEEDING CANOPY LIGHTING, FUEL PUMPS, AND FUEL DISPENSERS.
- 2 DIESEL FUEL DISPENSER SHALL BE REMOVED, CONDUITS SHALL BE REMOVED UP TO 5' AWAY FROM THE BUILDING. CONDUCTORS SHALL BE REMOVED BACK TO SOURCE.
- CANOPY FOR UNLEADED FUEL ISLANDS. REMOVE CANOPY AND ALL ATTACHED SYSTEMS. CONDUITS SHALL BE REMOVED UP TO 5' AWAY FROM THE BUILDING. CONDUCTORS SHALL BE REMOVED BACK TO SOURCE.
- 4 UNLEADED FUEL DISPENSER SHALL BE REMOVED. CONDUITS SHALL BE REMOVED UP TO 5' AWAY FROM THE BUILDING. CONDUCTORS SHALL BE REMOVED BACK TO SOURCE.
- 5 FUEL PUMPS SHALL BE REMOVED. CONDUITS SHALL BE REMOVED UP TO 5' AWAY FROM THE BUILDING. CONDUCTORS SHALL BE REMOVED BACK TO THE SOURCE.

AREA AND INFRASTRUCTURE TO BE DEMOLISHED

- DEMOLISH EXISTING GAS SERVICE ISLAND, DISPENSERS, KIOSK, ATTACHED SYSTEMS AND CANOPY.

÷


LEGEND:

DEMOLISH EXISTING GAS PIPING TO DISPENSERS

÷

e d

KENNEBUNK TRAVEL PLAZAS FUEL SYSTEM REPLACEMENT MILE 25.5 SB AND NB SOUTHBOUND PLAZA SITE PLAN – EXISTING GAS/DIESEL DEMOLITION SHEET NUMBER: M2 CONTRACT: 2018.18 38 OF 43



07/18

Drawn

GENERAL NOTES:

- THE 20,000 GALLON UNDERGROUND STORAGE TANKS (UST), SUMPS AND SUMP COVERS FOR THE SOUTHBOUND SERVICE PLAZA, ARE OWNER FURNISHED EQUIPMENT.
- THE SITE IS TO BE MADE READY PRIOR TO DECOMMISSIONING TEMPORARY, ABOVE GROUND FUEL STORAGE AND DISPENSING SYSTEMS. NO DEMOLITION OF TEMPORARY, ABOVE GROUND FUEL STORAGE AND DISPENSING SYSTEMS IS ALLOWED UNTIL THE PERMANENT, UNDERGROUND SYSTEMS ARE TESTED, COMMISSIONED AND OPERATIONAL
- 3. CONTRACTOR TO RELOCATE TEMPORARY FUEL EQUIPMENT TO OWNER DESIGNATED LOCATION.
- ALL FUEL LINES SHALL DRAIN BACK TO THE UNDERGROUND STORAGE TANKS AT MINIMUM 0.5% SLOPE. FUEL LINES SHALL MAINTAIN A MINIMUM 3-FEET OF COVER FROM TOP OF PIPE TO GRADE. SEE TYPICAL BURIED PIPING SECTION ON SHEET SC-01.
- 5. UST AND AST SYSTEMS ARE NOT TO BE RUN SIMULTANEOUSLY, USING THE SAME POWER SOURCE, UNLESS OTHERWISE DIRECTED BY THE OWNER. CONTRACTOR WILL BE ALLOWED UP TO A 24 HOUR SHUTDOWN PERIOD WITH A MINIMUM 7-DAY NOTICE GIVEN TO MTA RESIDENT ENGINEER AND APPROVAL FROM THE MTA ON A MUTUALLY AGREED UPON DATE FOR THE FOLLOWING:
 - A. SHUTDOWN #1: SHUTDOWN OF THE EXISTING UST SYSTEMS IN ORDER TO TEST AND COMMISSION THE NEW TEMPORARY AST SYSTEMS AND PUT THEM INTO FULL OPERATION
- B. SHUTDOWN #2: SHUTDOWN OF THE EXISTING AST SYSTEMS IN ORDER TO TEST AND COMMISSION THE NEW UST SYSTEMS AND PUT THEM INTO FULL OPERATION.

FLECTRICAL GENERAL NOTES:

- 1. CONTRACTOR SHALL DEVELOP AND COORDINATE A WORK SCHEDULE WITH MTA RESIDENT ENGINEER SEVEN (7) DAYS PRIOR TO BEGINNING ANY WORK. WORK SCHEDULE SHALL BE REEVALUATED ON A WEEKLY BASIS WITH MTA RESIDENT ENGINEER.
- CONTRACTOR IS RESPONSIBLE FOR PERFORMING A 30-DAY 2 LOAD STUDY TO ENSURE EXISTING ELECTRICAL INFRASTRUCTURE IS CAPABLE OF HANDLING ADDITIONAL LOADS. IF SYSTEM IS NOT CAPABLE CONTRACTOR IS RESPONSIBLE FOR PROVIDING TEMPORARY POWER.
- CONTRACTOR SHALL LIMIT ABOVEGROUND STORAGE TANK (AST) AND UNDERGROUND STORAGE TANK (UST) SIMULTANEOUS OPERATION TO NO MORE THAN 24 HOURS. CONTRACTOR SHALL COORDINATE SHUTDOWN TIME OF EXISTING/TEMPORARY EQUIPMENT WITH MTA RESIDENT ENGINEER FOR TESTING OF SYSTEM.
- 4. CONTRACTOR IS RESPONSIBLE FOR FIELD VERIFYING ALL EXISTING EQUIPMENT (CONDUIT RUNS, MATERIAL, ETC) FOR LOCATIONS AND SIZES BEFORE BEGINNING WORK CONTRACTOR SHALL CONFIRM RESPECTIVE DESIGN IS FEASIBLE BEFORE BEGINNING WORK.
- ALL WORK SHALL COMPLY WITH NFPA 70 (NATIONAL ELEGTRIC CODE), NFPA 30A (CODE FOR MOTOR FUEL DISPÉNSING FACILITIES AND REPAIR GARAGES) AND MAINE TURNPIKE DESIGN STANDARDS.
- 6. CONTRACTOR SHALL PROVIDE LABELS (BREAKER, CONDUIT, CONDUCTOR, ETC) AND UPDATED PANEL SCHEDULES FOR ALL WORK COMPLETED.

KEY NOTES:


- \langle 1 angle existing conduits shall be intercepted approximately 5 FEET OUTSIDE THE BUILDING AND USED FOR NEW RACEWAYS TO NEW AND TEMPORARY FUELING EQUIPMENT (PUMPS, DISPENSERS, LIGHTING, ETC).
 - (3) 2" GRS, AND (6) 1" GRS FOR COMMUNICATION (COMM TROUGH)
 - (1) 2" GRS, (4) 1-1/2" GRS FOR POWER (POWER TROUGH)
 - (1) 2" GRS FOR EXTERIOR LIGHTING (LB)

2 SERVICE ROOM HAS EXISTING CONDUITS STUBBED UP WITH SEAL-OFFS THAT TERMINATE TO RESPECTIVE TROUGHS. SERVICE ROOM HAS EXISTING 208/120V 3 PHASE PANEL WITH 225 AMP MAIN LUGS. THE EXISTING PANEL SHALL BE USED FOR NEW AND TEMPORARY FUELING EQUIPMENT (PUMPS, DISPENSERS, LIGHTING, ETC).


KENNEBUNK TRAVEL PLAZAS FUEL SYSTEM REPLACEMENT MILE 25.5 SB AND NB SOUTHBOUND PLAZA SITE PLAN – GAS/DIESEL PIPING SHEET NUMBER: M3

CONTRACT: 2018.18

39 OF 43




MTA	PROJECT	MANAGER:	Peter	S.	Merfeld.	P.



	<u>GENI</u>	ERAL NOTE:
ITING	1.	DUE TO THE EXISTENCE OF THE FUELING SYSTEM, IT IS ANTICIPATED CONTAMINATED SOILS WILL BE ENCOUNTERED AS PART OF THIS PROJECT. PRIOR TO CONSTRUCTION, CONTRACTOR SHALL REFER TO 'PROCEDURE FOR THE MANAGEMENT OF CONTAMINATED MATERIALS ENCOUNTERED DURING CONSTRUCTION' DOCUMENTATION.
_	<u>GENI</u>	ERAL ELECTRICAL NOTE:
11	1.	CONTRACTOR IS RESPONSIBLE FOR FIELD VERIFYING ALL EXISTING EQUIPMENT (CONDUIT RUNS, MATERIAL, ETC.) FOR LOCATIONS AND SIZES BEFORE BEGINNING WORK.
	<u>key</u>	NOTES:
	$\langle 1 \rangle$	SERVICE ROOM HAS ELECTRICAL PANEL FEEDING CANOPY LIGHTING, FUEL PUMPS, AND FUEL DISPENSERS.
	$\langle 2 \rangle$	DIESEL FUEL DISPENSER SHALL BE REMOVED, CONDUITS SHALL BE REMOVED UP TO 5' AWAY FROM THE BUILDING. CONDUCTORS SHALL BE REMOVED BACK TO SOURCE.
	$\langle 3 \rangle$	CANOPY FOR UNLEADED FUEL ISLANDS. REMOVE CANOPY AND ALL ATTACHED SYSTEMS. CONDUITS SHALL BE REMOVED UP TO 5' AWAY FROM THE BUILDING. CONDUCTORS SHALL BE REMOVED BACK TO SOURCE.
	4	UNLEADED FUEL DISPENSER SHALL BE REMOVED. CONDUITS SHALL BE REMOVED UP TO 5' AWAY FROM THE BUILDING. CONDUCTORS SHALL BE REMOVED BACK TO SOURCE.
	5	FUEL PUMPS SHALL BE REMOVED. CONDUITS SHALL BE REMOVED UP TO 5' AWAY FROM THE BUILDING. CONDUCTORS SHALL BE REMOVED BACK TO THE SOURCE.
		LEGEND:
,		AREA AND INFRASTRUCTURE TO BE DEMOLISHED

KENNEBUNK TRAVEL PLAZAS FUEL SYSTEM REPLACEMENT MILE 25.5 SB AND NB NORTHBOUND PLAZA SITE PLAN – EXISTING GAS/DIESEL DEMOLITION SHEET NUMBER: M5 CONTRACT: 2018.18 41 OF 43



GENERAL NOTES:

- THE 20,000 GALLON UNDERGROUND STORAGE TANKS (UST), SUMPS AND SUMP COVERS FOR THE NORTHBOUND SERVICE PLAZA, ARE OWNER FURNISHED EQUIPMENT.
- THE SITE IS TO BE MADE READY PRIOR TO DECOMMISSIONING TEMPORARY, ABOVE GROUND FUEL STORAGE AND DISPENSING SYSTEMS. NO DEMOLITION OF TEMPORARY, ABOVE GROUND FUEL STORAGE AND DISPENSING SYSTEMS IS ALLOWED UNTIL THE PERMANENT, UNDERGROUND SYSTEMS ARE TESTED, COMMISSIONED AND OPERATIONAL
- CONTRACTOR TO RELOCATE TEMPORARY FUEL EQUIPMENT TO OWNER DESIGNATED LOCATION.
- ALL FUEL LINES SHALL DRAIN BACK TO THE UNDERGROUND STORAGE TANKS AT MINIMUM 0.5% SLOPE. FUEL LINES SHALL MAINTAIN A MINIMUM 3-FEET OF COVER FROM TOP OF PIPE TO GRADE. SEE TYPICAL BURIED PIPING SECTION ON SHEET SC-01.
- 5. UST AND AST SYSTEMS ARE NOT TO BE RUN SIMULTANEOUSLY, USING THE SAME POWER SOURCE, UNLESS OTHERWISE DIRECTED BY THE OWNER. CONTRACTOR WILL BE ALLOWED UP TO A 24 HOUR SHUTDOWN PERIOD WITH A MINIMUM 7-DAY NOTICE GIVEN TO MTA RESIDENT ENGINEER AND APPROVAL FROM THE MTA ON A MUTUALLY AGREED UPON DATE FOR THE FOLLOWING:
 - A. SHUTDOWN #1: SHUTDOWN OF THE EXISTING UST SYSTEMS IN ORDER TO TEST AND COMMISSION THE NEW TEMPORARY AST SYSTEMS AND PUT THEM INTO FULL OPERATION
- B. SHUTDOWN #2: SHUTDOWN OF THE EXISTING AST SYSTEMS IN ORDER TO TEST AND COMMISSION THE NEW UST SYSTEMS AND PUT THEM INTO FULL OPERATION.

FLECTRICAL GENERAL NOTES:

- 1. CONTRACTOR SHALL DEVELOP AND COORDINATE A WORK SCHEDULE WITH MTA RESIDENT ENGINEER SEVEN (7) DAYS PRIOR TO BEGINNING ANY WORK. WORK SCHEDULE SHALL BE REEVALUATED ON A WEEKLY BASIS WITH MTA RESIDENT ENGINEER.
- 2. CONTRACTOR IS RESPONSIBLE FOR PERFORMING A 30-DAY LOAD STUDY TO ENSURE EXISTING ELECTRICAL INFRASTRUCTURE IS CAPABLE OF HANDLING ADDITIONAL LOADS. IF SYSTEM IS NOT CAPABLE CONTRACTOR IS RESPONSIBLE FOR PROVIDING TEMPORARY POWER.
- CONTRACTOR SHALL LIMIT ABOVEGROUND STORAGE TANK .3 (AST) AND UNDERGROUND STORAGE TANK (UST) SIMULTANEOUS OPERATION TO NO MORE THAN 24 HOURS. CONTRACTOR SHALL COORDINATE SHUTDOWN TIME OF EXISTING/TEMPORARY EQUIPMENT WITH MTA RESIDENT ENGINEER FOR TESTING OF SYSTEM.
- CONTRACTOR IS RESPONSIBLE FOR FIELD VERIFYING ALL EXISTING EQUIPMENT (CONDUIT RUNS, MATERIAL, ETC) FOR LOCATIONS AND SIZES BEFORE BEGINNING WORK CONTRACTOR SHALL CONFIRM RESPECTIVE DESIGN IS FEASIBLE BEFORE BEGINNING WORK.
- 5. ALL WORK SHALL COMPLY WITH NFPA 70 (NATIONAL ELEGTRIC CODE), NFPA 30A (CODE FOR MOTOR FUEL DISPENSING FACILITIES AND REPAIR GARAGES) AND MAINE TURNPIKE DESIGN STANDARDS.
- CONTRACTOR SHALL PROVIDE LABELS (BREAKER, CONDUIT, 6 CONDUCTOR, ETC) AND UPDATED PANEL SCHEDULES FOR ALL WORK COMPLETED.


KEY NOTES:

- EXISTING CONDUITS SHALL BE INTERCEPTED APPROXIMATELY 5 FEET OUTSIDE THE BUILDING AND USED FOR NEW RACEWAYS TO NEW AND TEMPORARY FUELING EQUIPMENT (PUMPS, DISPENSERS, LIGHTING, ETC).
 - (3) 2" GRS, AND (6) 1" GRS FOR COMMUNICATION (COMM TROUGH)
 - (1) 2" GRS, (4) 1-1/2" GRS FOR POWER (POWER TROUGH)
 - (1) 2" GRS FOR EXTERIOR LIGHTING (LB)
- 2. SERVICE ROOM HAS EXISTING CONDUITS STUBBED UP WITH SEAL-OFFS THAT TERMINATE TO RESPECTIVE TROUGHS. SERVICE ROOM HAS EXISTING 208/120V 3 PHASE PANEL WITH 225 AMP MAIN LUGS. THE EXISTING PANEL SHALL BE USED FOR NEW AND TEMPORARY FUELING EQUIPMENT (PUMPS, DISPENSERS, LIGHTING, ETC).

KENNEBUNK TRAVEL PLAZAS FUEL SYSTEM REPLACEMENT MILE 25.5 SB AND NB NORTHBOUND PLAZA SITE PLAN – GAS/DIESEL PIPING

CONTRACT: 2018.18

SHEET NUMBER: M6



43 OF 43