



# MAINE TURNPIKE AUTHORITY

DANIEL E. WATHEN, CHAIR ROBERT D. STONE, VICE CHAIR MICHAEL J.CIANCHETTE, MEMBER ANN R. ROBINSON, MEMBER THOMAS J. ZUKE, MEMBER BRUCE A. VAN NOTE, MEMBER EX-OFFICIO

S. PETER MILLS, EXECUTIVE DIRECTOR

**CONTRACT 2020.01** PAVEMENT REHABILITATION AND SAFETY IMPROVEMENTS MM 35.3 TO MM 42.0

> **CONTRACT 2020.01** PAVEMENT REHABILITATION AND SAFETY IMPROVEMENTS MM 35.3 TO MM 42.0

**LOCATION MAP** 

CHIEF OPERATIONS OFFICER

MAINE TURNPIKE AUTHORITY

STEPHEN R. TARTRE P.E. DIRECTOR OF ENGINEERING AND BUILDING MAINTENANCE

PORTSMOUTH





#### **INDEX OF SHEETS** DESCRIPTION SHEET NO. TITLE SHEET **GENERAL NOTES & ESTIMATED QUANTITIES** TYPICAL SECTIONS DRAINAGE PATH DETAILS BERM CORRECTIONS MEDIAN RESTORATION PAVEMENT MARKINGS MAINTENANCE OF TRAFFIC DETAILS TRAFFIC CONTROL MAINLINE CLOSURE 9-10 TRAFFIC CONTROL LANE CLOSURE AT EXIT RAMPS 11-12 TRAFFIC CONTROL LANE CLOSURE AT ENTRANCE RAMPS 15 TRAFFIC CONTROL EXIT RAMP CLOSURE TRAFFIC CONTROL ADVANCED SIGNING LOCATIONS MAINTENANCE OF TRAFFIC - SIGN SUMMARY

APPENDIX A - RUMBLE STRIP LAYOUT PLAN

2020.0

# **TY:LIN**INTERNATIONAL

PROJECT MANAGER

12/20/2019 DATE ENGINEER OF RECORD 12/20/2019 DATE JAMES FERGUSON

ITEM NO.	ITEM	UNIT	TOTAL QUANTITY
202.202	REMOVING PAVEMENT SURFACE - MAINLINE	SY	328,600
202.2026	REMOVING PAVEMENT SURFACE - DRAINAGE PATHS	SF	12,500
202,205	RUMBLE STRIPS	EA	68,860
203.20	COMMON EXCAVATION	CY	325
211.50	MEDIAN RESTORATION	LF	31,600
304.14	AGGREGATE BASE COURSE GRAVEL - TYPE A	CY	160
403.2081	HOT MIX ASPHALT, 12.5 mm NOMINAL MAXIMUM SIZE (POLYMER MODIFIED)	T	31,750
403.211	HOT MIX ASPHALT (SHIMMING)	T	300
403.213	HOT MIX ASPHALT, 12.5 mm NOMINAL MAXIMUM SIZE BASE	T	175
409.152	BITUMINOUS TACK COAT TRACKLESS, APPLIED	G	19,850
419.30	SAWING BITUMINOUS PAVEMENT	T	525
424.323	ASPHALT RUBBER MASTIC CRACK SEALER - APPLIED	LB	45,400
470.08	BERM DROP OFF CORRECTION - GRINDINGS	T	125
470.081	BERM CORRECTION	LF	18,600
604.182	CLEAN EXISTING CATCH BASIN AND MANHOLE	EA	30
606.1351	TERMINAL END - ANCHORED END - 31" W-BEAM GUARDRAIL	EA	8
606.178	GUARDRAIL BEAM	LF	325
606.352	REFLECTORIZED BEAM GUARDRAIL DELINEATORS	EA	500
606.353	DELINEATOR POST	EA	5
606.3621	GUARDRAIL ADJUST, SINGLE RAIL	LF	19,500
606,3622	GUARDRAIL ADJUST, DOUBLE RAIL	LF	35,/50
606.471	SINGLE OFFSET BLOCK - W-BEAM	EA	55
606.48	SINGLE GALVANIZED STEEL POST	EA	5
610.08	PLAIN RIPRAP	CY	40
613.319	EROSION CONTROL BLANKET	SY	31,000
618.14	SEEDING METHOD #2	UN	650
619.12	MULCH	UN	650
620.58	EROSION CONTROL GEOTEXTILE	SY	110
627.73	TEMPORARY PAVEMENT MARKING TAPE	LF	10,450
627.78	TEMPORARY PAVEMENT MARKING LINE, WHITE OR YELLOW	LF	279,500
627.812	TEMPORARY RAISED PAVEMENT MARKERS	EΑ	13,950
627.94	PAVEMENT MARKING TAPE	LF	5,220
629.05	HAND LABOR, STRAIGHT TIME	HR	40
631.12	ALL PURPOSE EXCAVATOR (INCLUDING OPERATOR)	HR	25
631.133	SKID STEER (INCLUDING OPERATOR)	HR	20
631.172	TRUCK - LARGE (INCLUDING OPERATOR)	HR	25
631.32	CULVERT CLEANER (INCLUDING OPERATOR)	HR	10
631.36	FOREMAN	HR	25
			_
652.30	FLASHING ARROW BOARD	EA	8
652.331	DRUM	LS	/
652.35	CONSTRUCTION SIGNS	SF	3,210
652.361	MAINTENANCE OF TRAFFIC CONTROL DEVICES	LS	1
652.410	PORTABLE - CHANGEABLE MESSAGE SIGN	EA	4
652.45	TRUCK MOUNTED ATTENUATOR	CD	134
<i>652.452</i>	AUTOMATED TRAILER MOUNTED SPEED LIMIT SIGN	EA	2
			1
656.50 659.10	BALED HAY, IN PLACE MOBILIZATION	EA LS	240

ESTIMATED QUANTITIES

TOTAL

#### CONSTRUCTION NOTES:

606.278 TERMINAL END - ANCHORED END

STATION DIRECTION

1743-45 SB

1745-72 NB

1865-26 SB

1866-77 NB

1959-23 SB

1960-90 NB

2037-38 SB

2038-88 NB

610.08 PLAIN RIP RAP

#### NOTES.

- I. TERMINAL END ANCHORED END TO BE REPLACED
  IN MEDIAN UNDER BRIDGE SECTIONS.
- 2. LOCATIONS TO BE ADJUSTED OR FINALIZED IN FIELD BY RESIDENT.

### **GENERAL NOTES:**

- I. ALL WORK SHALL CONFORM TO THE 2014 MAINE DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR HIGHWAY AND BRIDGES, EXCEPT AS MODIFIED BY THE MAINE TURNPIKE AUTHORITY'S SUPPLEMENTAL SPECIFICATIONS AND SPECIAL PROVISIONS.
- 2. THE CONTRACTOR IS REQUIRED TO CALL DIG SAFE AT I-888-344-7233 AT LEAST 72 HOURS PRIOR TO START OF WORK.
- 3. THE CONTRACTOR SHALL NOTIFY THE RESIDENT 10 DAYS PRIOR TO CONSTRUCTION SO THE RESIDENT CAN ARRANGE FOR MAINE TURNPIKE UNDERGROUND UTILITY LOCATION. ALL PROPOSED SIGN LOCATIONS AND EXCAVATION LOCATIONS SHALL BE MARKED AT THE NOTIFICATION TIME. EXCAVATING WILL NOT BE PERMITTED UNTIL THE AUTHORITY HAS LOCATED AND MARKED ITS' UNDERGROUND UTILITIES. OR NOTIFIED THE RESIDENT THERE ARE NO UNDERGROUND UTILITIES IN THE MARKED AREAS.

THE AUTHORITY HAS PROGRAMMED TWO FIELD VISITS FOR MAINE TURNPIKE UTILITY COORDINATION ON THIS PROJECT. SHOULD THE CONTRACTOR NEED ADDITIONAL SIGN LOCATIONS AND/OR ADDITIONAL EXCAVATION LOCATIONS MARKED, OR SHOULD THE CONTRACTOR FAIL TO MAINTAIN THE AUTHORITY'S PREVIOUSLY ESTABLISHED DIG SMART MARKS, THE AUTHORITY SHALL DEDUCT THE ADDED MARKING COSTS FROM THE CONTRACTOR'S PAYMENTS.

- 4. EXCAVATIONS ACCOMPLISHED AS PART OF THIS PROJECT SHALL BE CONSTRUCTED IN ACCORDANCE WITH OSHA SUBPART P OF 29 CFR PART 1926.650-652 (CONSTRUCTION STANDARDS FOR EXCAVATIONS).
- 5. ALL STANDARD DETAILS SHALL BE IN CONFORMANCE WITH MAINE DEPARTMENT OF TRANSPORTATION (MAINE DOT) STANDARD DETAILS HIGHWAY AND BRIDGES 2014 LATEST REVISIONS AND MAINE DOT BEST MANAGMENT PRACTICES FOR EROSION AND SEDIMENT CONTROL LATEST REVISION UNLESS OTHERWISE INCLUDED IN THESE PLANS.
- 6. COMMON BORROW SHALL BE COMPACTED TO 90% OF ITS MAXIMUM DRY DENSITY AS DETERMINED BY THE MODIFIED PROCTOR. GRANULAR BORROW AND AGGREGATE SHALL BE COMPACTED TO 95% OF THEIR MAXIMUM DRY DENSITY AS DETERMINED BY THE MODIFIED PROCTOR.
- 7. ALL STATIONS ARE APPROXIMATE, LOCATIONS TO BE FINALIZED IN FIELD BY RESIDENT.

# DRAINAGE NOTES:

I. NO EXISTING DRAINAGE SHALL BE ABANDONED, REMOVED OR PLUGGED WITHOUT APPROVAL OF THE RESIDENT.

### EROSION CONTROL:

- I. ADDITIONAL MEASURES MAY BE PROPOSED BY THE CONTRACTOR DUE TO SITE OR WEATHER CONDITIONS.THE RESIDENT MAY DIRECT THE CONTRACTOR TO IMPLEMENT ADDITIONAL MEASURES.ANY ADDITIONAL MEASURES APPROVED BY THE RESIDENT WILL BE MEASURED FOR PAYMENT.
- 2. ALL TEMPORARY EROSION CONTROL DEVICES SHALL BE INSTALLED IN ACCORDANCE WITH THE MAINE DEPARTMENT OF TRANSPORTATION BEST MANAGEMENT PRACTICES.

\UUZ_	Scal	e: NOT TO SCALE			Designed by:		NINTE	ERNATIO	NC	AL
	No.	Revision	Ву	Date						
υ ·					CONSULTANT F	PROJEC	T MANAGER:	Jim Ferguson		
5						Ву	Date		Ву	Date
r lleriorne.					Designed	TWA	10/2019	Checked	JOF	12/2019
-[					Drawn	TWA	10/2019	In Charge of	JOF	12/2019

T.Y. Lin International
12 Northbrook Drive
Building A, Suite One
Falmouth, Maine 04105
TEL: (207) 781-4721
FAX: (207) 781-4753



THE GOLD STAR MEMORIAL HIGHWAY PAVEMENT REHABILITATION AND SAFETY IMPROVEMENTS


ESTIMATED QUANTITIES AND GENERAL NOTES

SHEET NUMBER: C-1

CONTRACT:2020.01

2 OF 21


MTA PROJECT MANAGER: Ralph C. Norwood, IV



# TEMPORARY BITUMINOUS RAMP

#### NOTES:

- I. HOT MIX ASPHALT FOR TEMPORARY RAMPS WILL NOT BE MEASURED FOR PAYMENT, BUT SHALL BE INCIDENTAL TO ITEM 403.2081.
- 2. REMOVAL OF TEMP. BITUMINOUS RAMPS WILL NOT BE MEASURED FOR PAYMENT, BUT SHALL BE INCIDENTAL TO ITEM 403.2081.




#### MEDIAN SHOULDER RECONSTRUCTION

STATION TO <u>STATION</u> **DIRECTION** <u>OFFSET</u> 2048+50 2050+00 SB SB LT. LT. 2054+75 2058+50

#### NOTES:

- I. OTHER LOCATIONS NB & SB TO BE DETERMINED BY RESIDENT AFTER MILLING OF SHOULDER HAS OCCURRED.
- 2. SURFACE PAVEMENT SHALL BE COMPLETED AT SAME TIME AS OTHER MAIN LINE SHOULDER PAVING.
- 3. ITEM 403.213 SHALL BE MACHINE PLACED.



PAVEMENT MILL & FILL NOT TO SCALE

#### PAVEMENT LEGEND:

- (A) = 13/4" HOT MIX ASPHALT 12.5 mm NOMINAL MAXIMUM SIZE (POLYMER MODIFIED).
- B = MILLING DEPTH VARIES TO ACHIEVE A
  13/4" DEPTH AT THE EDGES OF LANE BEING MILLED.
- C = DOUBLE LAYER OF TACK ON NOTCHED WEDGE
- BERM DROPOFF CORRECTION GRINDINGS (SEE DETAIL A, SHEET P-3).
- BERM DROPOFF CORRECTION GRINDINGS (SEE DETAIL B, SHEET P-3).
- (F) = LIMITS OF MILL AND FILL (40'-6").
- G = WHEN MEDIAN GUARDRAIL IS ADJACENT TO THE SHOULDER, MILL TO FACE OF RAIL, OR EDGE OF PAVEMENT, WHICHEVER IS THE LESSER OFFSET

- (H) = A COATING OF HOT RUBBERIZED ASPHALT (ASTM D6690 TYPE IV) SHALL BE APPLIED AT THE TOP SURFACE LIFT TO ALL TRANSVERSE BUTT JOINTS AND LONGITUDINAL JOINTS EXCEPT WHERE THE NOTCHED WEDGE IS USED. INCIDENTAL TO ITEM 403.2081
- () = MEDIAN RESTORATION/REHABILITATION (SEE DETAIL, SHEET P-4)

# NOTES:

- I. BITUMINOUS TACK COAT IS REQUIRED BETWEEN ALL LIFTS OF PAVEMENT.
  BITUMINOUS TACK COAT IS REQUIRED ON ALL EXISTING PAVED OR MILLED SURFACES PRIOR TO PLACING PROPOSED PAVEMENT.
- 2. CROWNS FOR ALL COURSES OF PAVEMENT SHALL BE STRAIGHT.
- 3. PAVEMENT DEPTHS AS SHOWN ON THE PLAN ARE INTENDED TO BE NOMINAL.
- 4. MILLED SURFACE SHALL BE CRACK SEALED AFTER MILLING TO BE PAID FOR UNDER ITEM 424.323.

cal_											_
ypic_	Scale:				Designed by:	:					
4_1		AS NOTED							$\sim$		
\004					I-Y-	LII	MINIE	ERNATI	OIN	IAL	
00	No.	Revision	Ву	Date							
											1
<u>.</u>					CONSULTANT F	PROJEC	T MANAGER:	Jim Ferguson			
Ω						By	Date		Ву	Date	
ilename:					Designed	JOF	7/2019	Checked	KSD	7/2019	1
ட					Drawn	SRD	7/2019	In Charge of	JOF	12/2019	

T.Y. Lin International 12 Northbrook Drive Building A, Suite One Falmouth, Maine 04105 TEL: (207) 781-4721 FAX: (207) 781-4753




THE GOLD STAR MEMORIAL HIGHWAY

PAVEMENT REHABILITATION AND SAFETY IMPROVEMENTS


TYPICAL SECTIONS


SHEET NUMBER: P-1

CONTRACT:2020.01









# NOTES:

500' (TYP.)

PLAN VIEW

- & MAINE TURNPIKE

SYEL

-BWLL

= DRAINAGE PATH MILLING

LEGEND

NB RDWY

= TRAVEL LANE MILLING

- I. IT IS INTENDED TO PLACE NEW DRAINAGE PATHS AT SAME LOCATIONS OF PREVIOUS PROJECT (CONTRACT 2009.01).
- 2. POINT "B" IS I" HIGHER THAN POINT "A".
- 3. LOW/HIGH POINT STATIONING IS SHOWN IN SCHEDULES ABOVE.
- 4. DRAINAGE PATH REQUIRED AT ALL LOW POINTS.

DRAINAGE PATH DETAILS

Scale: NOT TO SCALE **TY-LIN**INTERNATIONAL By Date Revision ONSULTANT PROJECT MANAGER: Jim Ferguson 
 Date
 By
 Date

 7/2019
 Checked
 SRD
 12/2019

 7/2019
 In Charge of
 JOF
 12/2019
 Designed

T.Y. Lin International 12 Northbrook Drive Building A, Suite One Falmouth, Maine 04105 TEL: (207) 781-4721 FAX: (207) 781-4753



THE GOLD STAR **MEMORIAL HIGHWAY** 

DRAINAGE PATH DETAILS

PAVEMENT REHABILITATION


AND SAFETY IMPROVEMENTS

SHEET NUMBER: P-2 4 OF 21


MTA PROJECT MANAGER: Ralph C. Norwood, IV

# <u>DETAIL B</u> <u>BERM DROPOFF CORRECTION WITH GUARDRAIL</u>

NOT TO SCALE




DETAIL A BERM DROPOFF CORRECTION WITHOUT GUARDRAIL NOT TO SCALE



DETAIL C BERM CORRECTION NOT TO SCALE

# NOTES:

- I. BERM DROPOFF CORRECTION WILL BE PLACED AT ALL LOCATIONS WHEN NEEDED UNLESS OTHERWISE DIRECTED BY THE RESIDENT.
- 2. BERM DROP OFF CORRECTION OF 3" OR MORE SHALL BE PLACED PRIOR TO SHIFTING TRAFFIC TO THE LANE ADJACENT TO THE SHOULDER REQUIRING CORRECTION.



T.Y. Lin International 12 Northbrook Drive Building A, Suite One Falmouth, Maine 04105 TEL: (207) 781-4721 FAX: (207) 781-4753



THE GOLD STAR

PAVEMENT REHABILITATION AND SAFETY IMPROVEMENTS

> BERM DROPOFF CORRECTION DETAILS

SHEET NUMBER: P-3

CONTRACT:2020.01

MEDIAN RESTORATION

# NOTES:

- I. TAPER SLOPE DOWN TO CATCH BASINS TO PREVENT DROP OFF.USE DEPTH GREATER THAN 8" IN TAPER SECTION IF REQUIRED.
- 2. HYDROSEEDING SHALL BE USED IN THE MEDIAN, NO STRAW OR HAY MULCH SHALL BE USED.
- 3. PAVEMENT REMAINING UNDER GUARDRAIL THAT WILL PREVENT SHEET FLOW FROM PROPOSED SHOULDER TO MEDIAN SHALL BE REMOVED. THIS IS INCLUDED AS PART OF THE MEDIAN RESTORATION ITEM \*

Scale:				Designed b	y:				
	NOT TO SCALE			T-Y	/LII	NINT	ERNATI	OΝ	IAL
No.	Revision	Ву	Date	1					
				CONSULTANT	PROJEC	T MANAGER:	Jim Ferguson		
					Ву	Date		Ву	Date
				Designed	JOF	7/2019	Checked	SRD	12/2019
				Drawn	TWA	9/2019	In Charge of	JOF	12/2019

T.Y. Lin International 12 Northbrook Drive Building A, Suite One Falmouth, Maine 04105 TEL: (207) 781-4721 FAX: (207) 781-4753




MTA PROJECT MANAGER: Ralph C. Norwood, IV

PAVEMENT REHABILITATION AND SAFETY IMPROVEMENTS

MEDIAN RESTORATION DETAIL

SHEET NUMBER: P-4

CONTRACT:2020.01




TEMP. PAVEMENT MARKINGS 3 LANE ROADWAY

- I. TEMPORARY PAVEMENT MARKINGS ON MILLED PAVEMENT SHALL BE 6" SOLID WHITE, BROKEN WHITE, AND SOLID YELLOW PAINT LINES.
- 2. SWEL AND SYEL SHALL BE TEMPORARY RAISED PAVEMENT MARKERS SPACED AT 10'-0" O.C. AND OFFSET FROM FINAL STRIPING LOCATION.
- 3. BWLL SHALL BE PAVEMENT MARKING TAPE. 3' PIECES SHALL BE PLACED AT 40'-0" O.C. AND OFFSET FROM FINAL STRIPING LOCATION.
- 4. FINAL PAINTED PAVEMENT MARKINGS WILL BE LAID OUT BY CONTRACTOR AND INSTALLED BY MTA. RESIDENT SHALL BE ALLOWED TO REVIEW LAYOUT.
- 5. ONCE FINAL PAINTED LINES ARE COMPLETED BY MTA, CONTRACTOR WILL REMOVE ALL TAPE AND RPMS.

# <u>LEGEND</u>

SYEL = SOLID YELLOW EDGE LINE (6" PAINT) SWEL = SOLID WHITE EDGE LINE (6" PAINT) BWLL = BROKEN WHITE LANE LINE (6" PAINT)

EOP = EDGE OF PAVEMENT



PAVEMENT MARKING DETAIL 3 LANE ROADWAY

# <u>NOTES:</u>

- I. PAVEMENT MARKINGS SHALL BE 6" WIDE LINES.
- 2. THE OFFSET DISTANCES SHOWN ARE MEASURED FROM THE CENTER
- 3. TO BE LAID OUT BY CONTRACTOR AND PAINTED BY M.T.A.

Jer													
ven	Scal	e:			Designed by:								
\001_Pavemer					T:Y:	LJI	NINTE	ERNATIO	ON	IAL			
\00	No.	Revision	Ву	Date									
:					CONSULTANT F	ROJEC	CT MANAGER:	Jim Ferguson					
ilename:						Ву	Date		Ву	Date	1		
ien					Designed	JOF	8/2019	Checked	SRD	12/2019	1		
ш.					Drawn	TWA	9/2019	In Charge of	JOF	12/2019			

T.Y. Lin International 12 Northbrook Drive Building A, Suite One Falmouth, Maine 04105 TEL: (207) 781-4721 FAX: (207) 781-4753




THE GOLD STAR **MEMORIAL HIGHWAY** 

PAVEMENT REHABILITATION AND SAFETY IMPROVEMENTS


PAVEMENT MARKING AND GROOVING DETAILS


SHEET NUMBER: P-5

CONTRACT:2020.01



<u>MAINLINE</u> BEGINNING OF WORK SIGNAGE





# <u>LEGEND</u>

= FLASHING ARROW BOARD

■ = CONSTRUCTION SIGN


= PORTABLE - CHANGEABLE MESSAGE SIGN

= DRUM SPACED AT 80' INTERVALS ON TANGENTS 40' INTERVALS ON TAPERS

= WORK AREA

# NOTES:

I. FOR SIGN DETAILS, SEE SIGN SUMMARY SHEET 2. TO BE USED DURING STOPPAGE OF TRAFFIC



T.Y. Lin International 12 Northbrook Drive Building A, Suite One Falmouth, Maine 04105 TEL: (207) 781-4721 FAX: (207) 781-4753




THE GOLD STAR **MEMORIAL HIGHWAY** 


PAVEMENT REHABILITATION AND SAFETY IMPROVEMENTS TRAFFIC CONTROL MAINLINE CLOSURE (1 OF 2)


SHEET NUMBER: M-2

CONTRACT:2020.01

MTA PROJECT MANAGER: Ralph C. Norwood, IV







# <u>MAINLINE CLOSURE</u> <u>PAVING AND MILLING OPERATIONS IN LANE 3</u>

### NOTES:

I. FOR SIGN DETAILS, SEE SIGN SUMMARY SHEET
2. TO BE USED DURING STOPPAGE OF TRAFFIC

### <u>LEGEND</u>

= FLASHING ARROW BOARD

■ = CONSTRUCTION SIGN

= PORTABLE - CHANGEABLE MESSAGE SIGN

O = DRUM SPACED AT 80' INTERVALS ON TANGENTS 40' INTERVALS ON TAPERS

= WORK AREA

Scal				Designed by:					
	NOT TO SCALE	-		T:Y:	LII	NINTE	ERNATI	ON	IAL
No.	Revision	Ву	Date						
				CONSULTANT F	PROJEC	T MANAGER:	Jim Ferguson		
					Ву	Date		Ву	Date
				Designed	MRM	10/2019	Checked	TSK	12/2019
				Drawn	MRM	10/2019	In Charge of	JOF	12/2019

T.Y. Lin International 12 Northbrook Drive Building A, Suite One Falmouth, Maine 04105 TEL: (207) 781-4721 FAX: (207) 781-4753




THE GOLD STAR MEMORIAL HIGHWAY PAVEMENT REHABILITATION AND SAFETY IMPROVEMENTS TRAFFIC CONTROL

MAINLINE CLOSURE (2 OF 2)

SHEET NUMBER: M-3 10 OF 21

MTA PROJECT MANAGER: Ralph C. Norwood, IV

CONTRACT:2020.01 10 OF 2



LANE LANE LANE 2.LANE CLOSURES AT ENTRANCE AND EXIT RAMPS MAY BE COMBINED IF APPROVED BY THE RESIDENT. 3. ALL M.O.T. DEVICES AND LOCATIONS NOT NOTED ON THIS SHEET SHALL BE AS NOTED ON "TRAFFIC CONTROL MAINLINE CLOSURE" SHEETS M-ITHROUGH M-3.

<u>LEGEND</u>

= FLASHING ARROW BOARD

■ = CONSTRUCTION SIGN

= PORTABLE - CHANGEABLE MESSAGE SIGN

= DRUM SPACED AT 80' INTERVALS ON TANGENTS 40' INTERVALS ON TAPERS

= WORK AREA

NOT TO SCALE **TYLIN**INTERNATIONAL By Date Revision ONSULTANT PROJECT MANAGER: Jim Ferguson 
 By
 Date
 By
 Date

 MRM
 10/2019
 Checked
 TSK
 12/2019

 MRM
 10/2019
 In Charge of
 JOF
 12/2019

T.Y. Lin International 12 Northbrook Drive Building A, Suite One Falmouth, Maine 04105 TEL: (207) 781-4721 FAX: (207) 781-4753

I. FOR SIGN DETAILS, SEE SIGN SUMMARY SHEETS.




THE GOLD STAR **MEMORIAL HIGHWAY** 


PAVEMENT REHABILITATION AND SAFETY IMPROVEMENTS

TRAFFIC CONTROL LANE CLOSURE AT EXIT RAMPS (1 OF 2)

MTA PROJECT MANAGER: Ralph C. Norwood, IV

SHEET NUMBER: M-4 11 OF 21





CONTRACT:2020.01

NOT TO SCALE **TYLIN**INTERNATIONAL By Date Revision ONSULTANT PROJECT MANAGER: Jim Ferguson 
 By
 Date
 By
 Date

 MRM
 10/2019
 Checked
 TSK
 12/2019

 MRM
 10/2019
 In Charge of
 JOF
 12/2019

T.Y. Lin International 12 Northbrook Drive Building A, Suite One Falmouth, Maine 04105 TEL: (207) 781-4721 FAX: (207) 781-4753



# THE GOLD STAR **MEMORIAL HIGHWAY**


PAVEMENT REHABILITATION AND SAFETY IMPROVEMENTS

TRAFFIC CONTROL

LANE CLOSURE AT EXIT RAMPS (2 OF 2)

SHEET NUMBER: M-5

MTA PROJECT MANAGER: Ralph C. Norwood, IV



Designed by:

NOT TO SCALE

TY-LININTERNATIONAL

No. Revision By Date

CONSULTANT PROJECT MANAGER: Jim Ferguson
By Date
By Date
Designed MRM 10/2019 Checked TSK 12/2019
Drawn MRM 10/2019 In Charge of JOF 12/2019

T.Y. Lin International
12 Northbrook Drive
Building A, Suite One
Falmouth, Maine 04105
TEL: (207) 781-4721
FAX: (207) 781-4753




THE GOLD STAR MEMORIAL HIGHWAY AND SAFETY IMPROVEMENTS

TRAFFIC CONTROL
LANE CLOSURE AT ENTRANCE RAMPS (1 OF 2)

SHEET NUMBER: M-6

MTA PROJECT MANAGER: Ralph C. Norwood, IV

CONTRACT:2020.01 13 OF 21



NOT TO SCALE

Revision

# **TY:LIN**INTERNATIONAL

ONSULTANT PROJECT MANAGER: Jim Ferguson Date By Date TSK 12/2019 
 MRM
 10/2019
 Checked
 TSK
 12/2019

 MRM
 10/2019
 In Charge of JOF
 12/2019

By Date

T.Y. Lin International 12 Northbrook Drive Building A, Suite One Falmouth, Maine 04105 TEL: (207) 781-4721 FAX: (207) 781-4753



# THE GOLD STAR MEMORIAL HIGHWAY


PAVEMENT REHABILITATION AND SAFETY IMPROVEMENTS

TRAFFIC CONTROL

LANE CLOSURE AT ENTRANCE RAMPS (2 OF 2)

SHEET NUMBER: M-7 CONTRACT:2020.01

MTA PROJECT MANAGER: Ralph C. Norwood, IV



Falmouth, Maine 04105

TEL: (207) 781-4721

FAX: (207) 781-4753

ONSULTANT PROJECT MANAGER: Jim Ferguson

Date

TWA 11/2019 Checked


TWA 11/2019 In Charge of JOF 12/2019


By Date TSK 12/2019

MTA PROJECT MANAGER: Ralph C. Norwood, IV

TRAFFIC CONTROL EXIT 36 SB ON RAMP CLOSURE

SHEET NUMBER: M-8 15 OF 21





#### NOTES:

FOR ALL ADVANCED SIGNING LOCATIONS, ADVANCED WARNING SIGNS SHALL BE PLACED COVERED 24 HOURS IN ADVANCED OF ANY MAINLINE WORK THAT WILL INVOLVE MILLED SURFACES, UNCOVERED BEFORE BEGINING OF WORK, AND SHALL BE REMOVED OR COVERED WHEN NO MILLED SURFACE IS PRESENT.

Designed by:

TY-LININTERNATIONAL

No. Revision By Date

CONSULTANT PROJECT MANAGER: Jim Ferguson

By Date

By Date

By Date

Designed TWA 11/2019 Checked TSK 12/2019

Drawn TWA 11/2019 In Charge of JOF 12/2019

T.Y. Lin International
12 Northbrook Drive
Building A, Suite One
Falmouth, Maine 04105
TEL: (207) 781-4721
FAX: (207) 781-4753



THE GOLD STAR MEMORIAL HIGHWAY


TRAFFIC CONTROL
ADVANCED SIGNING LOCATIONS (1 OF 2)

PAVEMENT REHABILITATION

AND SAFETY IMPROVEMENTS

SHEET NUMBER: M-9

CONTRACT: 2020.01 16 OF 21



				TEXT OF	MENSIONS	(INCHEC)	MIMBER	COL	OD			
IDENTIFI- CATION	SIZE	GN	TEXT	LETTER	VERTICAL		OF SIGNS	BACK-	LEGEND	BORDER RADIUS	AREA IN SQUARE	NOTES
NUMBER	WIDTH	HEIGHT		HEIGHT	SPACING	RTE. MKR.	REQUIRED	GROUND	BORDER	RADIUS	FEET	
CS-I	48"	36"	RAMP CLOSED	8" 8"	6"		4	ORANGE	BLACK		12.00 (48)	
CS-3	48"	<i>48</i> "	EXPECT STOPPED TRAFFIC	6" 6" 6"	4 <sup>n</sup> 4 <sup>n</sup>		8	ORANGE	BLACK		16.00 (128)	
CS4-9P	36"	<i>48</i> "	STAY IN LANE	7" 7" 7"	5.25" 5.25"		10	ORANGE	BLACK		12.00 (120)	
CS-II	48"	<i>48</i> "	NO STOPPING ON PAVEMENT	6" 6" 6"	4" 4"		10	ORANGE	BLACK		16.00 (160)	
CS-19	48"	48"	EXIT OPEN AHEAD	6" 6" 6"	4" 4"		2	ORANGE	BLACK		16.00 (32)	
CS-33	96"	36"	WATCH FOR TRUCKS ENTERING AND LEAVING WORK AREA	6" 6" 6"	4" 4"		4	ORANGE	BLACK		24.00 (96)	
CS-38	48"	<i>48</i> "	SINGLE LANE AHEAD	6" 6" 6"	4" 4"		2	ORANGE	BLACK		16.00 (32)	
CS-4I (NORTH) (SOUTH)	96"	<i>18</i> "	NORTHBOUND SOUTHBOUND	8C	5" 5"		6 6	ORANGE	BLACK		12.00 (72) 12.00 (72)	

IDENTIFI- CATION		E OF GN	TEXT					(INCH		NUMBER OF	COL BACK-	OR LEGEND	BORDER	AREA IN SQUARE	NOTES
NUMBER		HE IGHT		HEI	GHT	SPA	CING	RTE. S SH	MKR.	SĬĠNS REQUIRED	GROUND	BORDER	RADIUS	FEET	
E5-I	72"	60"	EXIT	CO H	ONFOI IGHW	RM TO	) "ST, GNS" -	ANDAI - 2009	RD	2	GREEN	WHITE		30.00 (60)	
E5-2 (OPEN) (OPEN AHE AD)	60"	48"	EXIT OPEN							2	ORANGE	BLACK		20.00 (40) 20.00 (40)	
G20-I	48"	24"	ROAD WORK NEXT 7 MILES							4	ORANGE	BLACK		8.00 (32)	
G20-2	48"	24"	END ROAD WORK							4	ORANGE	BLACK		8.00 (32)	
G20-5aP	48"	24"	WORK ZONE							8	ORANGE	BLACK		8.00 (64)	
MI-2	24"	24"	MTERSTATE 95							9	RED/ BLUE	WHITE		4.00 (36)	
м3-3	24"	12"	SOUTH							2	WHITE	BLACK		2.00 (4)	
RI-I	48"	48"	STOP							2	RED	WHITE		16.00 (32)	
RI-2	60°	6O*	YIELD							2	WHITE	RED		12.50 (25)	
R2-I	48"	60"	SPEED LIMIT 60							8	WHITE	BLACK		20.00 (160)	
R2-6aP	48"	24"	FINES DOUBLE	7	7	,	1	,	7	8	WHITE	BLACK		8.00 (64)	

CONTRACT:2020.01

- Q	Scal	e:			Designed by:					•
-014_		NOT TO SCALE			T-Y-	LII	NINTE	ERNATI	ON	AL
1012	No.	Revision	Ву	Date						
:					CONSULTANT F	ROJEC	T MANAGER:	Jim Ferguson		
r ilename:						Ву	Date		Ву	Date
iel					Designed	TWA	10/2019	Checked	TSK	12/2019
-					Drawn	TWA	10/2019	In Charge of	JOF	12/2019
-										

T.Y. Lin International
12 Northbrook Drive
Building A, Suite One
Falmouth, Maine 04105
TEL: (207) 781-4721 FAX: (207) 781-4753



THE GOLD STAR MEMORIAL HIGHWAY

PAVEMENT REHABILITATION AND SAFETY IMPROVEMENTS

MAINTENANCE OF TRAFFIC SIGN SUMMARY (1 OF 3)

SHEET NUMBER: M-11

MTA PROJECT MANAGER: Ralph C. Norwood, IV

				T.C.	/T D//	WENC.	IONC.	(INO)	(F.C.)	MUMBER	001	00			
IDENTIFI- CATION NUMBER	SI	OF GN HEIGHT	TEXT	1FT	(T DIII TER GHT	VFR	TCAL	ARI	ROW	NUMBER OF SIGNS REQUIRED	COL BACK- GROUND	LEGEND BORDER	BORDER RADIUS	AREA IN SQUARE FEET	NOTES
R2-I2	36"	54"	END WORK ZONE SPEED LIMIT	CO	EXT L ONFOF IGHWA 2012	RM TO AY SIO	) "STA GNS" -	4NDAF 2009	RD	8	WHITE	BLACK		13.5 (108)	
WI-4 (RIGHT) (LEFT)	48"	48"								2	ORANGE	BLACK		16.00 (32) 16.00 (32)	
W3-/	48"	48"								2	ORANGE	BLACK		16.00 (32)	
W3-2	48"	48"								2	ORANGE	BLACK		16.00 (32)	
W3-4	48"	48"	BE PREPARED TO STOP							8	ORANGE	BLACK		16.00 (128)	
W3-5	48"	48"	SPEED LIMIT 60	,	V	,	7	,	1	8	ORANGE	BLACK		16.00 (128)	

IDENTIFI- CATION		E OF 'GN	TEXT					(INCH		NUMBER OF SIGNS	COL BACK-	OR LEGEND	BORDER	AREA IN SQUARE	NOTES
NUMBER		HEIGHT		HEI	GHT	SPA	CING	RTE.	MKR.	REQUIRED		BORDER	RADIUS	FEET	
W4-1	48"	48"		C	ONFO.	RM T	) "ST. GNS" -	IS SH IANDAI - 2009 MENT	RD	2	ORANGE	BLACK		16.00 (32)	
W4-2 (LEFT) (RIGHT)	48"	48"								8 8	ORANGE	BLACK		16.00 (128) 16.00 (128)	
W8-II	48"	48"	UNEVEN							10	ORANGE	BLACK		16.00 (160)	
W8-15	48"	48"	GROOVED PAVEMENT							16	ORANGE	BLACK		16.00 (256)	
W8-I5P	30"	24"	<b>The second seco</b>							16	ORANGE	BLACK		5.00 (80)	
W16-9p	24"	12"	AHEAD	7	1	,	7	7	7	2	ORANGE	BLACK		2.00 (4)	

- Q	Scal	e:			Designed by:							
:-014_N	Scal	NOT TO SCALE			T.Y.	LII	NINTE	RNATI	ON	AL		
\012	No.	Revision	Ву	Date	]							
:												
<u>:</u>					CONSULTANT F	PROJEC	T MANAGER:	Jim Ferguson				
g						Ву	Date		Ву	Date		
ilename:					Designed	TWA	10/2019	Checked	TSK	12/2019		
4					Drawn	TWA	10/2019	In Charge of	JOF	12/2019		
•		ı				1	0 10	, go o	, , , ,	2010		

T.Y. Lin International 12 Northbrook Drive Building A, Suite One Falmouth, Maine 04105 TEL: (207) 781-4721 FAX: (207) 781-4753



THE GOLD STAR MEMORIAL HIGHWAY

PAVEMENT REHABILITATION AND SAFETY IMPROVEMENTS


MAINTENANCE OF TRAFFIC SIGN SUMMARY (2 OF 3)


SHEET NUMBER: M-12

CONTRACT:2020.01

MTA PROJECT MANAGER: Ralph C. Norwood, IV

IDENTIFI- CATION NUMBER	SIZE SI		TEXT		R VE	VSIONS RTICAL PACING	ARR	OW	NUMBER OF SIGNS REQUIRED	COL BACK- GROUND	OR LEGEND BORDER	BORDER RADIUS	AREA IN SQUARE FEET	NOTES
W2O-I (I MILE) (AHE AD)	48"	48"	ROAD WORK 1 MILE	TEXT DIMENSIONS SHALL CONFORM TO "STANDARD HIGHWAY SIGNS" - 2009 & 2012 SUPPLEMENT				8 7	ORANGE	BLACK		16.00 (128) 16.00 (112)		
W2O-5 (LEFT ½MILE) (RIGHT ½MILE) (RIGHT AHEAD)	48"	48"	LEFT LANE CLOSED 1/2 MILE						4 4 2	ORANGE	BLACK		16.00 (64) 16.00 (64) 16.00 (32)	
W20-5a (LEFT) (RIGHT)	48"	48"	2 RIGHT LANES CLOSED 1/2 MILE	٧		V	V		4	ORANGE	BLACK		16.00 (64) 16.00 (64)	
LOGO S	24"	24"	MAINE TURNPIKE	SEE DETAIL			/L		9	SEE DETAIL			4.00 (36)	





T.Y. Lin International 12 Northbrook Drive Building A, Suite One Falmouth, Maine 04105 TEL: (207) 781-4721 FAX: (207) 781-4753



PAVEMENT REHABILITATION AND SAFETY IMPROVEMENTS

MAINTENANCE OF TRAFFIC SIGN SUMMARY (3 OF 3)

SHEET NUMBER: M-13

MTA PROJECT MANAGER: Ralph C. Norwood, IV

20 OF 21

